This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION,

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Page 1 Revised June 10, 2003

> Well No. 32C

Operator Williams Exploration and Production Lease Name Rosa Unit

Location Of Well: Unit Letter D Sec 21 Twp 31N Rge 06W API # 30-0 300392724000

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	MV	Gas	Flow	TBG
Lower Completion	DK	Gas	Flow	T36

Pre-Flow Shut-In Pressure Data

ſ	Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
L	Completion	090 3.3.05	4 DAY	T-194 C. 199	<u> </u>
ſ	Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
	Completion	0910 8-3-05	7 Day	T-733	455-

Flow Test No. 1

Commenced a	t (hour, date)* O			Zone producii	ng (Upper or Lower):
		<u>410 3.</u>	7-05		<u> Lower</u>
Time	Lapsed Time	l Pre	<u>essure</u>	Prod. Z	Zone Remarks
(Hour, Date)	Since*	Upper Compl.	Lower Compl	l. Tem	np.
	***	T 198			
0910-3-8	1 DAy	C 204	T425	<u> </u>	· LAKELOOP COMP DOWN
· - 1		Taos			•
0910 3-9	2 Days	Call	T 474	28	Line Perss 300 NO Flow
	,	7 211		_	,
5910 3-10	3 DAYS	C 216	7 374	<u> </u>	Live FRSS 259#
	,	7 217			.4
11-3 aip	4 DAYS	C 221	T 429	30	Line Passo 251#
	,				
			_		20 20 70
	-				The constant

Production rate during test

Oil: ______BOPD based on _____Bbls. In _____Hrs. _ Gas: _____ MCFPD; Test thru (Orifice or Meter): _____ MCFPD

Mid Toot Churt In Dragging Data

		Ha- Lest Shat-In Llessare Da	ata Talia	THE PARTY OF THE P		
Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)		
Completion	0910 3-3-05	11 DAUS	Ta32 ca36			
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)		
Completion	0910 3-11-05	3 Days	T740_			

(Continue on reverse side)

<u> </u>			Flow Te	est No	o. 2			
Commenced	at (hour, date)**	09(0)	3-14-05	Zon	e producing (U	oper or Lower):	GOOFR:	
Time	Lapsed Time		essure		Prod. Zone	Remarks	· · · · · · · · · · · · · · · · · · ·	
(Hour, Date)	Since**	Upper Compl.	Lower Comp	1	Temp.	<u> </u>	. ng 3 m 11	
5910 3-15	1Day.	T 128	T 754		75	3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
1910 3-14	2 Days	T 139	T 769	, .	72	to the constitution		
71.5 0190	3 Days	T 138	T 780	,	68		german der en en	
910 3-18	4 Days	T 137 C 142	T 790		75	v		1. 11.
				,		"		11
	·				ing pathy		-	
roduction rate	during test		1-1 E	, ,	. 44-			en i Mari
)il:	BOPD based	l on D; Test thru (Orif	Bbls. In	•	Hrs	Grav	GOR	
ras:	MCFP.	D; Test thru (Orif	ice or Meter): _	<u> </u>	~ FTFR	· · · · · · · · · · · · · · · · · · ·	., .	
temarks:				•	1	-		
	•				v v			
hereby certify	that the informat	ion herein contain	ed is true and c	ompl	ete to the best o	f my knowledge.	Jes .	ing section of the se
pproved	MAR 3 1		20		. · · · · · · · · · · · · · · · · · · ·	Ullams F))
lew Mexico Oi	l Conservation D	ivision		· · -		-		- T. W
/	n //	3	•	: ,	By 15.\\	BEZURES		
y Charle	The				Title Sa	PROD TEC	L	
itle SU	PERVISOR DIST	RICT#3		- -	E-mail Addres	s bill. beeve	es Qwillia	<u>ms .Co</u> .
:				-	Date	18-05	jar komo o	· · · · · · · · · · · · · · · · · · ·

Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when earth requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period; at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).