

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-08527 ✓
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator ConocoPhillips Company ✓		6. State Oil & Gas Lease No. B-1423-1
3. Address of Operator P.O. Box 51810 Midland, TX 79710		7. Lease Name or Unit Agreement Name East Vacuum GSA Unit Tr 2819 ✓
4. Well Location Unit Letter G : 1980 feet from the North line and 1980 feet from the East line Section 28 Township 17-S Range 35-E NMPM County Lea ✓		8. Well Number 003 ✓
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3961' RKB		9. OGRID Number 217817
		10. Pool name or Wildcat Vacuum (GB/SA)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

E-PERMITTING <SWD INJECTION>
CONVERSION ☐ RBDMS ☐
RETURN TO ☐ TA ☐
CSNG ☐ CHG LOC ☐
INT TO P&A ☒ P&A NR ☐ P&A R ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

POOH W/ RBP. 4260' - 3700'
--MIRU. ND WH. NU BOP.
--RIH Tbg - Tag RBP @ 4,100'. Circ hole w/ MLF. Spot 50sx cmt to 3,700'. WOC-Tag
--Spot 25sx cmt @ 3,200' - 3,050'. WOC-Tag
170' --Perf @ 1,810' - Sqz 65sx cmt to 1,597'. WOC-Tag
--Perf @ 250' - Circ 80sx cmt to surface
--POOH. Fill wellbore. Verify cmt @ surface in all annuli

**The Oil Conservation Division
MUST BE NOTIFIED 24 Hours
Prior to the beginning of operations**


****A closed-loop system will be used for all fluids from this wellbore and disposed of required by OCD Rule 19.15.17****

Spud Date:

5/24/39


Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE P&A Tech - Basic Energy Services DATE 3/17/15

Type or print name Greg Bryant E-mail address: _____ PHONE: 432-563-3355

For State Use Only

APPROVED BY:  TITLE Dist. Supervisor DATE 3/23/2015

Conditions of Approval (if any):

MAR 26 2015

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations

Date: March 9, 2015

RKB @ 3961'
 DF @ 3956'
 GF @ 3951'

Subarea : Buckeye
 Lease & Well No. : East Vacuum GB/SA Unit, Tract 2819 003
 Legal Description : 1980 FNL & 1980 FEL, Sec. 28, T-17S, R-35E
 County : Lea State : New Mexico
 Field : Vacuum (Grayburg-San Andres)
 Date Spudded : 5/24/1939 Rig Released: _____
 API Number : 30-025-08527
 Status: Producing
 Drilled as State N # 3 State Lease No. B-1423-1
 OGRID 01764

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
OH 4300-4681	2/16/1950	5% HCL	3000					
OH 4300-4681	5/25/1952	15% HCL	11,500					
OH 4300-4681	8/25/1960	CO to 4681'						
OH 4300-4681	8/27/1960	15% M38	1000					
OH 4300-4681	11/9/1960	LO	30,000	30,000				
OH 4300-4681	12/30/1971	GW	28,000	56,000				
	1/3/1972	Ran 4" Liner @ 4227-4680'						
OH 4300-4681	3/6/1973	15% HCL	300					
OH 4300-4681	7/6/1990	Toulene/Pentol	7000					
	9/28/1994	Tag fill @ 4389'; CO to 4625'						
OH 4300-4681	10/4/1994	Red Acid	2000					
	10/1/1996	Tag fill @ 4623'						
OH 4300-4681	10/3/1996	15% Fercheck	8000					
	2/17/2015	Csg lk fr 2820-2851'						
	2/19/2015	Sqz csg w/ 8.35 bbl slurry						
	2/24/2015	Tag Cmt @ 2345; DO & fell out @ 2824'						
	3/2/2015	Set CIBP @ 4260'						
	3/5/2015	Set RBP @ 4100'						

11" Hole

8 5/8" 32# SS @ 1647'
 Cmt'd w/ 650 sxs, circ
 TOC @ Surface

Top Salt @ 1760'

Sqz Csg lk fr 2820-2851' w/ 8.35 bbls slurry

TOC 5 1/2" @ 3000' (calc)

Base Salt @ 3128'

RBP @ 4100'

4" Liner @ 4227-4680'
 CIBP @ 4260'
 7 7/8" Hole
 5 1/2" 14# SS @ 4300'
 Cmt'd w/ 275 sxs
 TOC @ 3000' (calc)

4 3/4" Open Hole
 4300-4681'

Formation Tops:

Rustler
 Yates
 Queen
 Grayburg
 San Andres
 Glorieta


← POOH. w/ RBP

PBTD @ 4625'
 TD @ 4681'

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations

Date: March 9, 2015

RKB @ 3961'
DF @ 3956'
GF @ 3951'



11" Hole

P&S 80sx cmt @ 250'-3'

8 5/8" 32# SS @ 1647'

Cmt'd w/ 650 sxs, circ

TOC @ Surface

P&S 65sx cmt @ 1810'-1597' - Tag

Top Salt @ 1760'

Sqz Csg lk fr 2820-2851' w/ 8.35 bbls slurry

TOC 5 1/2" @ 3000' (calc)

Spot 25sx cmt @ 3200'-3050' - Tag

Base Salt @ 3128'

Spot 50sx cmt @ 4100'-3700' - Tag

RBP @ 4100'

4" Liner @ 4227-4680'

CIBP @ 4260'

7 7/8" Hole

5 1/2" 14# SS @ 4300'

Cmt'd w/ 275 sxs

TOC @ 3000' (calc)

4 3/4" Open Hole

4300-4681'

PBTD @ 4625'
TD @ 4681'

Subarea : Buckeye
Lease & Well No. : East Vacuum GB/SA Unit, Tract 2819 003
Legal Description : 1980 FNL & 1980 FEL, Sec. 28, T-17S, R-35E
County : Lea State : New Mexico
Field : Vacuum (Grayburg-San Andres)
Date Spudded : 5/24/1939 Rig Released :
API Number : 30-025-08527
Status : Producing
Drilled as State N # 3 State Lease No. B-1423-1
OGRID 01764

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
OH 4300-4681	2/16/1950	5% HCL	3000					
OH 4300-4681	5/25/1952	15% HCL	11,500					
OH 4300-4681	8/25/1960	CO to 4681'						
OH 4300-4681	8/27/1960	15% M38	1000					
OH 4300-4681	11/9/1960	LO	30,000	30,000				
OH 4300-4681	12/30/1971	GW	28,000	56,000				
	1/3/1972	Ran 4" Liner @ 4227-4680'						
OH 4300-4681	3/6/1973	15% HCL	300					
OH 4300-4681	7/6/1990	Toulene/Pentol	7000					
	9/28/1994	Tag fill @ 4389'; CO to 4625'						
OH 4300-4681	10/4/1994	Red Acid	2000					
	10/1/1996	Tag fill @ 4623'						
OH 4300-4681	10/3/1996	15% Fercheck	8000					
	2/17/2015	Csg lk fr 2820-2851'						
	2/19/2015	Sqz csg w/ 8.35 bbl slurry						
	2/24/2015	Tag Cmt @ 2345'; DO & fell out @ 2824'						
	3/2/2015	Set CIBP @ 4260'						
	3/5/2015	Set RBP @ 4100'						

*SPOT CMT
4260' - 3700'*

Formation Tops:

Rustler
Yates
Queen
Grayburg
San Andres
Glorieta