Submit 1 Copy To Appropriate District Office District I - (575) 393-6161 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Energy, Minerals and Natural Resourd District II - (575) 748-1283 OIL CONSERVATOR BESISTOR 811 S. First St., Artesia, NM 88210 District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV - (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM Santa Fe, NME97 505 2019 SUNDRY NOTICES AND REPORTS ON SEEVED SUNDRY NOTICES AND REPORTS ON SEEVED DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other 2. Name of Operator Mewbourne Oil Company	WELL API NO. 30-025-45400 5. Indicate Type of Lease STATE FEE 6. State Oil & Gas Lease No. 7. Lease Name or Unit Agreement Name
3. Address of Operator	10. Pool name or Wildcat
PO Box 5270, Hobbs NM 88241 4. Well Location	Grama Ridge; Bone Spring 28435
Unit Letter _E: _2435feet from theNorth line and _600feet from theWest line	
Section 25 Township 21S Range 34	
11. Elevation (Show whether DR, RKB, RT, C 3697' GL	GR, etc.)
	SUBSEQUENT REPORT OF: L WORK ALTERING CASING CE DRILLING OPNS. PAND A CEMENT JOB CEMENT JOB CEMENT JOB CEMENT JOB CEMENT JOB CEMENT dates, including estimated date iple Completions: Attach wellbore diagram of
 O8/05/19 Spud 17 ½" hole. TD 17 ½" hole @ 1815'. Ran 1800' of 13 ¾" 54.5# J55 ST&C Csg. Cemented with 900 sks Class C w/additives. Mixed @ 12.0#/g w/2.49 yd. Tail w/200 sks Class C Neat. Mixed @ 14.8#/g w/1.32 yd. Displaced w/271 bbls of BW. Plug down @ 7:00 PM 08/07/19. Circ 270 sks of cmt to the pit. Test BOPE to 5000# & Annular to 3500#. At 1:15 A.M. 08/08/19, tested csg to 1500# for 30 mins, held OK. FIT test to 10.5 PPG EMW. Drilled out with 12 ¼" bit. O8/12/19 TD 12 ¼" hole @ 5715'. Ran 5700' of 9 ½" 40# J55 LT&C & 40# HCL80 Csg. Cmt 1st stage with 400 sks Lite Class C (50:50:10) w/additives. Mixed @ 11.5#/g w/2.69 yd. Tail w/200 sks Class C w/additives. Mixed @ 14.8#/g w/1.32 yd. Plug down @ 10:15 PM 08/12/19. Set ECP w/2075#. Drop bomb & open DV tool w/700#. Circ 177 sks of cmt off of DV tool. Cmt 2nd stage w/750 sks Lite Class C (50:50:10) w/additives. Mixed @ 11.5#/g w/2.69 yd. Tail w/200 sks Class C Neat. Mixed @ 14.8#/g w/1.32 yd. Plug down @ 2:00 A.M. 08/13/19. Circ 45 sks of cmt to the pit. Set Cameron mandrel hanger through BOP w/180k#. At 3:30 P.M. 08/13/19, tested csg to 1500# for 30 mins, held OK. FIT test to 9.5 PPG EMW. Drilled out with 8 ¾" bit. 	
Spud Date: 08/05/19 Rig Release Date:	
I harshy cartify that the information shove is true and complete to the best of my knowledge and helief	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE	
APPROVED BY:	

.

1