Submit I Copy To Appropriate DistrictState of New MexicoForm C-102OfficeEnergy, Minerals and Natural ResourcesRevised July 18, 201	
1625 N. French Dr., Hobbs, NM 88240	Ĩ
811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION 5. Indicate Type of Lease	4
District III – (505) 334-6178 1220 South St. Francis STATE FEE	
1220 S. St. Francis Dr., Santa Fe, NM	
SUNDRY NOTICES AND REPORTS ON WITH S	-
(DO NOT LISE THIS FORM FOR DRODOSALS TO DRILL OR TO DEEDEN OR DIACOACK TO A	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) YARROW 32 STATE 1. Type of Well: Oil Well S Gas Well Other 8. Well Number #204H	
2. Name of Operator 9. OGRID Number 7377	
3. Address of Operator 10. Pool name or Wildcat	1
P O BOX 2267, MIDLAND TX 79702 59900 TRIPLE X; BONE SPRING	
4. Well Location Unit Letter O	
Section 32 Township 23S Range 33E NMPM County LEA CO	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
3672 GL	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS.	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB	
OTHER: DTHER: DRILL CSG	<u> </u>
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated da of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	te
proposed completion or recompletion.	
08/10/19 20" CONDUCTOR @ 120' 08/23/19 17-1/2" HOLE	
08/23/19 Surface Casing @ 1,392' Ran 13-3/8" 54.5# J-55 STC	
Lead Cement w/ 1,153 sx Class C(1.73 yld, 13.5 ppg), Trail w/ 231 sx Class C (1.33 yld, 14.8 ppg) Test casing to 1,500 psi for 30 min - OK. Circ 811 sx cement to surface Resume Drillin 12-1/4" hole	
08/27/19 12-1/4" ohle 08/27/19 1st Intermediate Casing @ 5,221'	
Ran 9-5/8", 40# J-55 LTC (0' - 4,156') Ran 9 5/8" 40# HCK-55 LTC (4,156' - 5,221')	
Lead Cement w/ 1,129 sx Class C (2.32 yld, 12.7 ppg), Trail w/ 290 sx Class C (1.42 yld, 14.8 ppg) Test casing to 2,230 psi for 30 min -Good Circ 315 sx cement to surface Resume Drilling 8-3/4" hole	
Spud Date: 08/23/19 Rig Release Date:	
Spud Date: 08/23/19 Rig Release Date.	
	_
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE MA DULLE Sr. Regulatory Administrator DATE 09/03/19	
	_
For State Lise Only	-
Petroleum En :	
APPROVED BY:	_

(