

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

DISTRICT II

811 South First, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

1220 South St. Francis Dr., Santa Fe, NM 87505

**OIL CONSERVATION DIVISION**  
1220 South St. Francis Drive  
Santa Fe, NM 87505

WELL API NO.

30-025-36305

5. Indicate Type of Lease

☒ STATE

☐ FEE

6. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

☒ OIL WELL

☐ GAS WELL

☐ OTHER

2. Name of Operator

Apache Corporation

3. Address of Operator

6120 South Yale, Suite 1500 Tulsa, OK 74136

4. Well Location

Unit Letter D : 1240 Feet From The NORTH Line and 1270 Feet From The WEST Line  
Section 16 Township 21S Range 37E NMPM County LEA

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

GR 3479

7. Lease Name or Unit Agreement Name

STATE C TRACT 12

8. Well No.

14

9. Pool name or Wildcat

PENROSE SKELLY; GRAYBURG (50350)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

**SUBSEQUENT REPORT OF:**

☐ Perform Remedial Work

☐ Plug and Abandon

☐ Temporarily Abandon

☐ Change Plans

☐ Pull or Alter Casing

☐ Other

☐ Remedial Work

☐ Altering Casing

☐ Commence Drilling Operations

☐ Plug and Abandonment

☐ Casing Test and Cement Job

☒ Other

SPUD, SURF CSG, TD, PROD. CSG.

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/24/2003

MIRU CAPSTAR RIG #8. SPUD 12-1/4" HOLE. DRILL & SURVEY TO 1132'. RIH W/ 8-5/8" 24# J55 ST&C CSG. CEMENT SHOE AT 1276' W/ 550 SX CLASS C + 2% CACL + 1/8# CELLO FLAKE = 60 BBLs 14.8 PPG SLURRY W/ 1.35 CF/SX YIELD. CIRC 232 SX CEMENT TO PIT. WOC.

7/24 - 8/7/2003

DRILL & SURVEY 1276' - 6950'. CIRCULATE FOR LOGS

8/7/2003

RUN LOGS. RIH W/ 5-1/2" 17# J55 LT&C CSG. CEMENT SHOE @ 6950' W/ 775 SX 50:50 POZ: CLASS C W/ 10% GEL + 5% SALT + 0.125 #/SX CELLO FLAKE = 337 BBLs 11.8 PPG SLURRY W/ 2.44 CF/SX YIELD. TAIL W/ 500 SX 50:50 POZ: CLASS C W/ 2% GEL + 5% SALT = 115 BBLs 14.2 PPG SLURRY W/ 1.29 CF/SX YIELD. CIRC 126 SX CMT TO PIT. RELEASE RIG 5:00 AM 8/7/2003

AUG 2003  
RECEIVED  
Hobbs  
OCD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Michelle L. Hanson*

TITLE

TECH. COORDINATOR - DRLG. DATE 8/12/2003

TYPE OR PRINT NAME

MICHELLE L HANSON

TELEPHONE NO. (918) 491-4900

(This space for State Use)

APPROVED BY

*Gay W. Winick*

TITLE

FIELD REPRESENTATIVE II/STAFF MANAGER

DATE

AUG 19 2003

CONDITIONS OF APPROVAL, IF ANY: