

District I 1625 N. French Dr., Hobbs, NM 88240
District II 1301 W. Grand Ave., Artesia, NM 88210
District III 1000 Rio Brazos Rd., Aztec, NM 87410
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

WELL API NO. 30-025-07757
5. Indicate Type of Lease STATE [ ] FEE [X]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name M. J. Raley
8. Well Number 2
9. OGRID Number 000495
10. Pool name or Wildcat West Nadine Paddock Blinbry/Drinkard/Ab


SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well [X] Gas Well [ ] Other [ ]
2. Name of Operator Amerada Hess Corporation
3. Address of Operator P.O. Box 840, Seminole, Texas 79360-0840

4. Well Location Unit Letter M : 330 feet from the South line and 330 feet from the West line
Section 8 Township 20S Range 38E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3563' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK [ ] PLUG AND ABANDON [ ]
TEMPORARILY ABANDON [ ] CHANGE PLANS [ ]
PULL OR ALTER CASING [ ] MULTIPLE COMPLETION [ ]
OTHER: [ ]
SUBSEQUENT REPORT OF: REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS. [ ] PLUG AND ABANDONMENT [ ]
CASING TEST AND CEMENT JOB [ ]
OTHER: Install and cement liner [X]



13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08/11/2003 thru 08/24/2003

MIRU Tyler Well Service PU & TOH w/production tbg. Set CIBP @ 5850'. TOH w/rods and pump. Installed 6" 900 BOP. RU Bull Rogers & TIH w/ 1 - 4 1/2" csg shoe, 2 jts of 4 1/2" FL-4S 11.60# csg liner, 1 - 4 1/2" float collar & 134 jts of 4 1/2" FL-4S 11.6# csg liner. RU Halliburton, mixed & pumped 140 sks premium plus cement @ 14.8 lb/gal. Removed 6" 900 BOP. Cut 4 1/2" csg stub & installed 10" 900 x 6" 600 tbg spool & 6" 600 BOP. TIH w/ 3 7/8" bit, bit sub, 6 - 3 1/8" drill collars & 170 jts 2 3/8" tbg to 5420'. Drill float collar @ 5744', 2 jts of 4 1/2" liner, float shoe @ 5837' & CIBP @ 5850'. TIH w/total of 237 jts of 2 3/8" tbg to 7553'. TOH w/tbg. RU BJ Services, TIH w/ 4 1/2" pkr & 185 jts of 2 3/8" tbg. Set pkr @ 5775'. Acidized well with 3000 gals 15% HCL. Scale squeezed and returned well to pump.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carol J. Moore TITLE Prod Acct Tech DATE 08/25/2003

Type or print name Carol J. Moore Telephone No. (432)758-6738 (This space for State use)

APPROVED BY Gary W. Wink OFFICE REPRESENTATIVE II/STAFF MANAGER DATE

Conditions of approval, if any

AUG 27 2003