Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD-HOBBS

FORM APPROVED OMB No. 1004-0135 Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

5. Lease Serial No.

Do not use this form for proposals to utili of the cites an	NM-59392
Do not use this form for proposals to drill or re enter an abandoned well. Use Form 3160-3 (APD) for such proposals.	6. If Indian, Allottee or Tribe Name N/A
SUBMIT IN TRIPLICATE - Other instructions on reverse side	7. If Unit or CA/Agreement, Name and/or No.
SUBMIT IN TRIPLICATE - Other instructions on Tovolog end	N/A
Type of Well Gas Well Other	8, Well Name and No.
X Oil Well Gas Weil Other	Lusk AHB Federal 1
Name of Operator	9. API Well No.
Yates Petroleum Corporation 3b. Phone No. (include area code)	30-025-30808
105 S. 4th Str., Artesia, NM 88210 505-748-1471	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., OR Survey Description)	Wildcat Yates
800' FNL & 1650' FEL Unit B Sec. 35-T19S-R32E	11. County or Parish, State Lea County, NM
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE.	
TYPE OF SUBMISSION TYPE OF ACTION	ON
Produc	ction (Start/Resume) Water Shut-Off
Acidize	THE STATE OF THE S
Notice of Intent Alter Casing Practite Teat	
X Cubacquent Report	1991011
Change Plans Plug and Abandon Plugand Abandon	orarily Abandon T Disposal
Final Abandonment Notice Convert to Injection Plug Back Water 3. Describe Proposed of Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work if the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent repo	and approximate duration there of all pertinent markers and zones.
Attach the Bond under which the work will be performed or provide the Bond No. on tile with BL.Wichia. Required subsequent of following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been determined that the site is ready for final inspection.)	orts shall be filed within 30 days a Form 3160-4 shall be filed once in completed, and the operator has
testing has been completed. Final Abandonment Notices shall be lifed only after all requirements of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @	1732425262
testing has been completed. Final Abandonment Notices shall be lifed only after all requirements of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation.	3200'. Pressured up to
testing has been completed. Final Abandonment Notices shall be filled unity after all requirements of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls.	9292 72 ETT (11) and 3085-3092' (8)
testing has been completed. Final Abandonment Notices shall be lifed unity after all requirements of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls.	9292 tz Et 10 3200'. Pressured up to (11) and 3085-3092' (8)
testing has been completed. Final Abandonment Notices shall be lifed only after all requirements of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand w	9292 tz Et 10 3200'. Pressured up to (11) and 3085-3092' (8)
testing has been completed. Final Abandonment Notices shall be lifed only after all requirements determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v 2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION.	9292 72 ETT (11) and 3085-3092' (8) W/Expedite.
testing has been completed. Final Abandonment Notices shall be filled unity after all requirements determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v 2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION.	9252 tz ETT (9252 tz ETT) (11) and 3085-3092' (8) W/Expedite.
testing has been completed. Final Abandonment Notices shall be filled unity after all requirements determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v 2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION.	9292 72 27 77 79 3200'. Pressured up to (11) and 3085-3092' (8) W/Expedite.
testing has been completed. Final Abandonment Notices shall be filled unity after an requirement that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v/2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION. 14. Thereby certify that the foregoing is true and correct Name (Printed/Typed) Stormi Davis Title Regulatory Co.	2) 3200'. Pressured up to (11) and 3085-3092' (8) W/Expedite.
testing has been completed. Final Abandonment Notices shall be lifed unity arter an requirement determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v 2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION. 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Stormi Davis Title Regulatory Co	2 3200'. Pressured up to (11) and 3085-3092' (8) W/Expedite. compliance Technician ACCEPTED FOR RECOR
testing has been completed. Final Abandonment Notices shall be lifed only after an expension of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v 2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION. 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Stormi Davis Title Regulatory Co	2 3200'. Pressured up to (11) and 3085-3092' (8) W/Expedite. compliance Technician ACCEPTED FOR RECOR
testing has been completed. Final Abandonment Notices shall be lined drilly after an expension of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v 2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION. 14. Thereby certify that the foregoing is true and correct Name (Printed/Typed) Stormi Davis Title Regulatory Co	ompliance Technician ACCEPTED FOR RECOR SEE SOLUTION ACCEPTED FOR RECOR ACCEPTED
testing has been completed. Final Abandonment Notices shall be lined drily after an expension of determined that the site is ready for final inspection.) 9-18-06 Set 5-1/2" CIBP @ 4530' and capped w/35' cement. Perforated 4 holes @ 1500#. No circulation. 9-19-06 Perforated Yates (1 JSPF) 2969-2980' (12), 3012-3021' (10), 3060-3070' w/total of 41 .42" holes. Acidized w/2500 gal 15% NEFE w/60 balls. 9-23-06 Frac Yates w/27000 gal SilverStim LT R-13 w/49000# 16/30 Brady sand v 2-7/8" tubing @ 3141' WELL IS BACK ON PRODUCTION. 14. Thereby certify that the foregoing is true and correct Name (Printed/Typed) Stormi Davis Title Regulatory Co	29252 tz ETT (11) and 3085-3092' (8) W/Expedite. Compliance Technician ACCEPTED FOR RECOR USE WESLEY WINGRAM

Lusk AHB Federal 1 API No. 30-025-30808 Yates Petroleum Corporation Addendum to Sundry November 16, 2006

Note addendum for 9-18-06

The 100' plug was not set at 3200 feet due to no circulation and proximity of perforated zone.

When well is Plugged and Abandoned, the plug for the Yates perforations must extend past the perforations at 3200 feet.

WWI 111606