Submit 3 Copies To Appropriate District Office	State of New			Form C-103
District I	Energy, Minerals and I	Natural Resources		May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II	OIL GOMERNMAN		WELL API NO. 30-041-20923	
1301 W. Grand Ave., Artesia, NM 88210			5. Indicate Type of Lease	
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	MO Pio Prozos Pd. Artes NM 97410		STATE FEE	
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	220 C C4 Fernais De Comta Fe NB4		6. State Oil & Gas Lease No.	
87505		The state of the s	n/a	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				r Unit Agreement Name
1. Type of Well: Oil Well Gas Well Other Plug & Abandon			8. Well Number 1	
2. Name of Operator MANZANO, LLC			9. OGRID Numb 231429	er
3. Address of Operator P.O. BOX 2107 – ROSWELL, NM 88202-2107			10. Pool name or Wildcat Wildcat	
4. Well Location				
Unit Letter J :1980 feet from the SOUTH line and 1980 feet from the EAST line				
Section 6 Township 7S Range 33E NMPM ROOSEVELT County				
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4436'gr				
Pit or Below-grade Tank Application or Closure				
Pit typeDepth to GroundwaterDistance from nearest fresh water wellDistance from nearest surface water				
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INT		i.	_	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	SEQUENT REF	PORT OF: ALTERING CASING []
-	CHANGE PLANS	COMMENCE DRIL		PANDA S
-	MULTIPLE COMPL	CASING/CEMENT		
OTHER:	П	0.71.17		
OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: The state of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.				
04/24/06 MI & RU UNITED DRILLING RIG #28 – SPUD IN DRILLING 17 ½' HOLE @ 4:00PM – TD 17 ½" HOLE @ 398'				
- KAN 9 JOINTS (397') 13 3/8" 48#/FT H-40 ST&C CASING W/TEXAS PATTERN GUIDE SHOE & INSERT FLOAT - RIL BI				
SERVICES & CEMENT W/450sx CLASS "C" CEMENT, PLUG DOWN @ 10:30AM (4/25/06), CIRCULATE 121sx TO PITS - WOC				
CUT OFF 13 3/8" CASING, WELD ON 13 3/8" WELLHEAD, TEST BOPE TO 500#, START DRILLING ON SHOE @ 11:00pm 4/25/06, START DRILLING NEW 11" HOLE @ 12:30am ON 4/26/06				
05/01/06 TD 11" HOLE @ 3750' @ 1:45PM – RUN 3753' 8 5/8" 32#/ft J55 LT&C CASING W/GUIDE SHOE & FLOAT				
COLLAR TO TD - RU BJ SERVICES & CEMENT W/950sx 35/65/6 CLASS "C" + 250sx CLASS "C". PLUG DOWN @ 11:00AM				
ON 5/02/06, CIRCULATE 210sx TO PITS – WOC, CUT OFF CASING, NU WELLHEAD & BOP & TEST BOPE TO 1500#, START DRILLING ON SHOE @ 12:30am 5/03/06, START DRILLING NEW 7 7/8" HOLE @ 2:00am 5/3/06				
DRILLING ON SHOE @ 12:30am 5/0	33/06, START DRILLING N	EW 7 7/8" HOLE @ 2:0	00am 5/3/06	
05/21/06 TD 7 7/8" @ 9650' -	- RU SCHLUMBERGER & F	RUN OPEN HOLE LOG	S - PLUG & ABA	ANDON AS PER
NMOCD INSTRUCTIONS AS FOLL	OWS: PLUG #1-25sx CLASS	S.C.@ 9550', PLUG #2-	25sx CLASS C @ "	7645' DI LIG #2.25gy
CLASS C @ 5645', PLUG #4-25sx Cl @ 338', Plug #7-10sk CLASS C SURI	LASS C @ 3685 (TAG @ 368 FACE PLUG – RELEASE RI	85'), PLUG #5-25sx CL. G @ 6:00PM 5/24/06	ASS C @ 1950', PI	LUG #6-25sx CLASS C
		_		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan .				
SIGNATURE	Janay TITLE			5/28/07
1		MANA	MGER	DATE 01/03/06'
Type or print name: MIKE HANAGAN For State Use Only	I E-mail	address: mhanagan@dfr	n.com Tele	phone No. 505-623-1996
ADDDOVED DV.			JU	N 0 7 2007
APPROVED BY: Conditions of Approval (if any)	TITLE			DATE. ZOU!
Conditions of Approval (if any): Approved as to plugging of the Well Bore. THE OIL CONSERVATION DIVISION MUST				
Liability under bond is retained unit BE NOTIPIED 24 HOURS PRICE				
surface restoration is completed. BEGINNING OF PLUGGING OPENIONS.				