District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe office.

Form C-144 June 1, 2004

Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

Type of action: Registration of a pit or below-grade tank Covered by a general plant in the low-grade tank Covered by a general plant i		
Operator: E.O.G. Resources Telephone: 432) 686-3600 e-mail address:		
Facility or well name: DK (1 1 1 1 2 2 2 3 1 1 1 1 1 1 1 1 1 1 1 1	Longitude	NAD: 1927 1983
County: Rose vel Latitude Latitude Longitude NAD: 1927 1983 Surface Owner: Federal State Private Indian		
Pit Below-grade tank Volume:bbl Type of fluid:		
Lined \(\sqrt{\text{Unlined}}\) Unlined \(\sqrt{\text{Unlined}}\)	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic Thickness 12 mil Clay		
Pit Volumebbl		
The volume	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more //OC	(0 points)
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No)	(0 points)
water source, or less than 1000 feet from all other water sources.)	(10)	(o points)
Distance to surface water (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)
	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite offsite. If offsite, name of facility		
(5) Attach soil sample results and a diagram of sample locations and excavations.		
* Refer to AHACLED pit Closure Plantette		
APR 0 4 2008		
HORRSOCH		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I fur ther certify that the above-described free below-grade tank has been/will be constructed or closed according to NMOCD guidelines. A general permit , or an (attached) alternative OCD-approved plan		
Date. 3/27/08 Printed Name/Title Dusta L. Wilson Field Manager Signature		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval. Printed Name/Title Signature ENVIRONMENTAL ENGINEER Date: 4-4-08		

P.O. Box 310 Hobbs, NM 88241-0310

505.392.8584 Hobbs. New Mexico Cell 505.631.2442 Fax 505.392.3085

Hobbs, New Mexico

Reserve Pit Remediation

SURFACE PIT CLOSURE PLAN

PIT PARAMETERS

COMPANY: EOG Resources Inc.

WELL SITE: Bull Moose 2 State #1H

LEGAL DESCRIPTION: Unit M Sec 2 T8s R37e, 760 FSL

760 FWL, Roosevelt co.

The reserve pit inset on this leasehold is being permitted to close as per New Mexico OCD "Pit and Below Grade Tank Guidelines" dated November 1, 2004.

This pit was excavated and formed to the dimensions roughly 150' X 180' X 6' deep. A 12 mil membrane liner and pad was used to prevent leakage to the surface soils. A visual examination of the membrane liner indicates that the liner had maintained its integrity.

After the drilling and completion phase of this project, the water phase of the pit contents were pumped and hauled to an approved water injection facility. It is estimated that the volume of solids remaining are to +/- 2200 yards. The burial cell is to be excavated and lined with a minimum 12 mil membrane that complies with ASTM Standards: D-5747, D-5199, D-5994, and D-4833. The cuttings will be loaded as to allow for > 36" freeboard to ground level. After the cuttings are loaded the 12 mil liner will be folded over the top, and a 20 mil minimum thickness liner meeting the minimum requirements as outlined in ASTM Standard Methods: D-5747, D-5199, D-5994, D-4833; will be used to cap and cover to an extended area that exceeds three feet in all directions from the

edge of the burial cell. This cap will be constructed as to slope and allow for water runoff from burial cell.

A minimum of 36" of top soil will be used to cover the burial cell. This soil must be capable of supporting plant growth. A seed mixture will be used as to conform to local BLM and OCD requirements.

After the drilling solids are buried, the natural contour of the surrounding soils will be mechanically shaped as to prevent erosion of the well site until vegetation is established.

LOCATION DIAGRAM

EOG RESOURCES, Bull Moose 2 State #1H API #30-041-20935 V-DOOR EAST

