Submit 3 Copies To Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources				Form C-103
District I 1625 N. French Dr., Hobbs, NM 88240				WELL API NO.	May 27, 2004
District II	OIL CONSERVATION DIVISION			······································	30-025-38596
1301 W. Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.			5. Indicate Type	
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505			STATE 6. State Oil & G	FEE X
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	•			o. State On & G	as Lease Ivo.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				Jones	or Unit Agreement Name
1. Type of Well: Oil Well X Gas Well Other				8. Well Number 001	
Name of Operator     Pierce Production Company, L.L.C				9. OGRID Num	ber 017733
3. Address of Operator P. O. Box 2079				10. Pool name or Wildcat	
Midland, Texas 79702-2079				Brunson Drinkard Abo - South	
4. Well Location					
Unit Letter L : 1980 feet from the South line and 330 feet from the West line					
Section 6 Township 22S Range 38E NMPM CountyLea  11. Elevation (Show whether DR, RKB, RT, GR, etc.)					
	3356' GR	einei DR,	, KK <i>D</i> , K1, OK, etc.)		
Pit or Below-grade Tank Application 🔲 o	r Closure 🔲				
Pit typeDepth to GroundwaterDistance from nearest fresh water well Distance from nearest surface water					
Pit Liner Thickness: mil	Below-Grade Tank: Volu	ıme	bbls; Cons	struction Material_	`
12. Check A	Appropriate Box to Ind	icate N	ature of Notice, R	eport or Other	r Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR					ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DRILL	_	P AND A
PULL OR ALTER CASING	•		CASING/CEMENT		
OTHER:			OTHER:		
13. Describe proposed or comp	oleted operations. (Clearly	state all		give pertinent da	tes, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.					
MIRU O'Ryan Drilling Company Rig #4. Spudded 12 1/4" surface hole @ 4:00 PM CSDST 10-29-07. Drilled 12 1/4" surface hole to depth of 1,342' KB measurement. Ran 35 joints of 9 5/8", 36#, J-55, 8rd LTC new API surface casing and set @ 1,342' KB measurement. BJ Services cemented w/285 sacks of Class "C" Lite Pozmix (65:35) cement containing 6% gel + .25 pps Cello Flake + 2% calcium chloride mixed @ 12.8 ppg, mixing water 9.76 gps, yield 1.83 cu. ft./sack followed by 200 sacks of Class "C" neet cement containing 2% calcium chloride mixed @ 14.8 ppg, mixing water 1.34 gps, yield 1.34 cu. ft./sack. Circulated 98 sacks of cement to closed loop container system.					
I hereby certify that the information grade tank has been/will be constructed or					
SIGNATURE H	Truck	TTLE <u>Vi</u>	ce President - Enginee	ering	DATE <u>03/25/2008</u>
Type or print name Bill Pierce For State Use Only	E	E-mail ad	ldress:bill@piercepro	duction.net T	Felephone No. (432)570-6009
APPROVED BY:	W T	TTLE	(spalmist		DATE
Conditions of Approval (if any):	<u>'</u>		<u> </u>		DUIT