Office District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	te of New Mexico erals and Natural Resources SERVATION DIVISION South St. Francis Dr. eta Fe, NM 87505	Form C-103 May 27, 2004 WELL API NO. 30-025-38752 5. Indicate Type of Lease STATE FEE 6. State Oil & Gas Lease No. VA-2137
SUNDRY NOTICES AND REPOR (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other 2. Name of Operator	HOBBS OCE	7. Lease Name or Unit Agreement Name Boots State Unit 8. Well Number 9. OGRID Number 025575 10. Pool name or Wildcat Eight Mile Draw; Permo Upper Penn
Unit Letter N : 660 feet from the South line and 2310 feet from the West line Section 17 Township 11S Range 35E NMPM Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
Pit or Below-grade Tank Application □ or Closure □		
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABAN TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMP	SUB REMEDIAL WOR COMMENCE DRI	SEQUENT REPORT OF: K
OTHER:	☐ OTHER: Produ	ction Casing
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
4/21/08 TD 10,600'. 4/25/08 Set cement plug 9200-9100' – 61 sx Class H + 0.2% D13 + 0.65% D65 (wt 17, yld 0.99, H2O mix 3.77). Set cement plug 7900-7500' – 206 sx Class H + 0.65 D65 + 0.1% D13 (wt 17, yld 99, H2O mix 3.77). 4/26/08 thru 4/28/08 Tagged cement @ 7560'. Drilled cement plugs from 7560-7670'. 4/29/08 Prep to sidetrack original hole. KOP @ 7.670'. 5/10/08 Reached TD @ 9400'. Set 5-1/2" 17# J-55 & HCP-110 csg @ 9400'. Float collar @ 9356'. Cemented w/925 sx 35:65:6 Poz H + 0.2% D13 + 0.2% D167 + 6% D20 + 0.2% D46 (yld 1.91, wt 12.7). Tailed in w/426 sx Pecos Valley Lite + 0.3% D167 + 1.33% D44 + 0.4% D46 + 0.2% D65 + 0.4% D800 (yld 1.41, wt 13).		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-		
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.		
SIGNATURE (114)	TITLE Regulatory Complia	nce Technician DATE 5/30/08
Type or print name Allison Barton	E-mail address: <u>abarton @ypcr</u>	m.com Telephone No. (575) 748-1471
	OC DISTRICT SUPERVISOR/GEN	- in. U (.F()
APPROVED BY:		