# District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 R10 Brazos R0ad. Aztec, NM 87410 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

For closed-loop systems that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office.

Form C-144 CLEZ

July 21, 2008

1220 South St. Francis Dr. Santa Fe, NM 87505

Closed-Loop System Permit or Closure Plan Application

(that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

Type of action: Permit Closure

Instructions: Please submit one application (Form C-144 CLEZ) per individual closed-loop system request. For any application request other than for a closed-loop system that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, please submit a Form C-144.

	opose to implement waste removal for closure, pieuse suomina i orin C-144	
Please be advised that approval of this request does not relieve the operator of liability environment. Nor does approval relieve the operator of its responsibility to comply wi	should operations result in pollution of surface water, ground water or the ith any other applicable governmental authority's rules, regulations or ordinances.	
Operator: Cimarex Energy Co. of Colorado	OGRID#: 162683	
Address: PO Box 140907; Irving, TX 75014-0907		
Facility or well name: Smith No. 4		
Facility or well name: Smith No. 4  API Number: 30-025- 39158 OCD F	Permit Number:	
U/L or Qtr/Qtr I Section 25 Township 19S Range 33E		
Center of Proposed Design: Latitude 32°37' 42.36" Longitude 103°36' 33.18" NAD: ☐ 1927 ☐ 1983		
Surface Owner:   Federal   State   Private   Tribal Trust or Indian Allotn	· · · · · · · · · · · · · · · · · · ·	
Closed-loop System: Subsection H of 19.15.17.11 NMAC     Operation: ☑ Drilling a new well ☐ Workover or Drilling (Applies to activitie ☐ Above Ground Steel Tanks or ☑ Haul-off Bins	es which require prior approval of a permit or notice of intent)   P&A	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergent Signed in compliance with 19.15.3.103 NMAC	ncy telephone numbers	
Closed-loop Systems Permit Application Attachment Checklist: Subsection Instructions: Each of the following items must be attached to the application. attached.      □ Design Plan - based upon the appropriate requirements of 19.15.17.11 No. □ Operating and Maintenance Plan - based upon the appropriate requirement □ Closure Plan (Please complete Box 5) - based upon the appropriate requirement □ Previously Approved Design (attach copy of design) API Number: □ Previously Approved Design (attach copy of design)	MAC  the of 19.15.17.12 NMAC  rements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Previously Approved Operating and Maintenance Plan API Number:		
S.  Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Instructions: Please indentify the facility or facilities for the disposal of liquid facilities are required.  Disposal Facility Name: CRI	ds, drilling fluids and drill cuttings. Use attachment if more than two  Disposal Facility Permit Number:	
Disposal Facility Name:	Disposal Facility Permit Number:	
Will any of the proposed closed-loop system operations and associated activitie  ☐ Yes (If yes, please provide the information below) ☑ No	s occur on or in areas that will not be used for future service and operations?	
Required for impacted areas which will not be used for future service and operation Soil Backfill and Cover Design Specifications based upon the appropriate Re-vegetation Plan - based upon the appropriate requirements of Subsect Site Reclamation Plan - based upon the appropriate requirements of Subsect	riate requirements of Subsection H of 19.15.17.13 NMAC ion I of 19.15.17.13 NMAC	
6. Operator Application Cortifications		
Operator Application Certification:  I hereby certify that the information submitted with this application is true, acc	urate and complete to the best of my knowledge and belief.	
Name (Print): Natalie Krueger	Title: Reg Analyst	
Signature: Dalate Surger	Date: 9.17.2008	
e-mail address: <u>nkrueger@cimarex.com</u>	Telephone: 469-831-5829	

7.		
7.  OCD Approval: Permit Application (including closure plan) Closure F	Plan (only)	
OCD Representative Signature:	Approval Date: 9/18/08	
Title: Geologist	OCD Permit Number: PL-DD472	
8.  Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report.  The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date:		
0		
Closure Report Regarding Waste Removal Closure For Closed-loop Systems Instructions: Please indentify the facility or facilities for where the liquids, dri two facilities were utilized.		
Disposal Facility Name:	Disposal Facility Permit Number:	
Disposal Facility Name:	Disposal Facility Permit Number:	
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?  Yes (If yes, please demonstrate compliance to the items below) \( \subseteq \text{No} \)		
Required for impacted areas which will not be used for future service and operat  Site Reclamation (Photo Documentation)  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique	ions:	
10.		
Operator Closure Certification:	All a services at the first of	
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.		
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone:	

## Cimarex Energy Co. - Closed-Loop System Design Plan

## **Equipment List**

- Primary Shakers
- Mud Cleaner hydro-cyclones
- 1 or 2 Centrifuges (depending on well depth)
- De-watering system with pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing (may not be necessary for shallower wells)
- Drying Augur
- Sump Drying Augur
- Sump
- Cuttings Boxes
- Reserve Fluids Tank Farm
- Wire Mesh Trash Enclosure (spent motor oils kept in separate containers and later sent to approved landfill)

## **Operation and Maintenance**

The Cimarex Zero Discharge system is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This ensures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

These closed loop operations can be monitored by our service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and tested for all regulated toxic materials. If found they are removed and disposed of per regulatory requirements.

## Closure Plan

During drilling operations, all liquids, drilling fluids, and cuttings will be hauled off via CRI (Controlled Recovery Incorporated, Permit R-9166).



# Closed Loop with Drying Auger and Dewatering System

