

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-025-07388-4 <b>07384</b>
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE
State Oil & Gas Lease No.

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	Lease Name or Unit Agreement Name North Hobbs (G/Sa) Unit
Name of Operator Occidental Permian, LTD	Well No. 232
Address of Operator 1017 Stanoliad Rd. Hobbs New Mexico 88240	Pool name or Wildcat Hobbs (G/SA)
Well Location Unit Letter <b>K</b> : <b>1325</b> Feet From The <b>South</b> Line and <b>1325</b> Feet From The <b>West</b> Line Section <b>20</b> Township <b>18 S</b> Range <b>38 E</b> NMPM <b>Lea</b> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) <b>3656' GR</b>	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER: <input type="checkbox"/>	

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ANBANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/25/03 Tagged existing CIBP @ 3957'. Spot 35 sks of c cement @ 3957'. Tagged @ 3725'. Circ. well w/ plugging mud.

11/26/03 Perf @ 2440'. Pressured up on perfs to 1000 psi. Spot 25 sks of cement @ 2490'. Tagged @ 2280'. Perf @ 1665'. Pressured up on perfs to 1000 psi. Spot 25 sks of cement @ 1695'. Tagged @ 1388'

11/27/03 Perf @ 300' Squeezed 110 sks of cement, no circ. Tagged @ 159' Perf @ 60' Circ. 75 sks of cement down 7" up annulus to surface. Close in under 550 psi pressure.

Cut off wellhead and anchors 3' BGL. Capped well. Installed dry hole marker.

Approved as to plugging of the Well Bore.  
Liability under bond is retained until  
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert Gilbert TITLE SR Engr Tech DATE 12-24-03  
TYPE OR PRINT NAME ROBERT GILBERT TELEPHONE NO. 397-8206

(This space for State Use)

APPROVED BY

Harry W. Wink

OC FIELD REPRESENTATIVE II/STAFF MANAGER

TITLE

DATE JAN 02 2004

CONDITIONS OF APPROVAL, IF ANY: