

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

OCT 02 2008

HOBBS

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-041-20933

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.  
n/a

7. Lease Name or Unit Agreement Name

Geneva-Fee

8. Well Number 1

9. OGRID Number 231429

10. Pool name or Wildcat  
CHAVEROO, PERMO PENN, NORTH

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

MANZANO, LLC

3. Address of Operator

P.O. BOX 2107 - ROSWELL, NM 88202-2107

4. Well Location

Unit Letter K : 1650 feet from the SOUTH line and 2310 feet from the WEST line

Section 33 Township 6S Range 33E NMPM County ROOSEVELT

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4,396' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/16/09

Plug and abandon well as follows:

12.5#

1. Displace hole w/9.5#/gl w/25# salt gel per barrel
2. Pump 25 sack plug from 7000' to 7200' (top perf @ 7266') **WOC & TAG**
3. Pump 25 sack shoe plug from 3650' - 3850' (8 5/8" shoe @ 3740') & tag
4. Pump 25 sack plug from 1700' - 1900' (Top salt @ 1950')
5. Pump 25 sack plug from 285' - 485' (13 3/8" shoe @ 385) & tag
4. Pump 10 sack surface plug from 0'-75' & set dry hole marker

PERF @ 50' 25 SACKS  
@ 435'

PERF @ 60' CIRC  
CMT TO SURFACE

The Oil Conservation Division **Must be notified**  
**24 hours prior** to the beginning of plugging operations

Spud Date:

1/15/07

Rig Release Date:

2/16/07

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*[Signature]*

TITLE Engineer

DATE 9/25/09

Type or print name Kyle Alpers

E-mail address: kjalpers@qwestoffice.net

PHONE: 575-623-1996

For State Use Only

APPROVED BY:

*[Signature]*

TITLE

*[Signature]*

DATE 10/23/2009

Conditions of Approval (if any):



**MANZANO - LLC**  
**WELLBORE Diagram**

**GENEVA FEE #1**

API # 30-041-20933  
 1650' FSL & 2310' FWL  
 Sec. 33, T6S, R-33E  
 Roosevelt County, NM  
 GL Elevation: 4396'  
 KB Elevation: 4411' (15')

TOC @ 200' (Differential Press.)

13 3/8" 48#/ft H40 @ 385'  
 Cemented w/450sx Class "C"  
 Circulate 162 sx

8 5/8" 24 & 32 #/ft @ 3740'  
 Cement w/1250sx Class "C"  
 Circulate 320sx



Dry Hole Marker

Proposed 10sk plug from surface to 75'

9.5#/gl salt gel between plugs

17 1/2" Hole  
 Proposed 25sk plug from 285'-485'

9.5#/gl salt gel between plugs  
 Proposed 25sk plug from 1700'-1900'

9.5#/gl salt gel between plugs

11" Hole  
 Proposed 25sk plug from 3650'-3850'

9.5#/gl salt gel between plugs

Proposed 25sk plug from 7000'-7200'

Perforations @ 7266'-7272'

CIBP @ 7675' w/35' cement

Perforations @ 7758'-7759'

CIBP @ 7910' w/35' cement

Perforations @ 8264'-8307'

DV Tool @ 8376'

CIBP @ 8365' w/35' cement

Perforations @ 8438'-8442'

CIBP @ 8800' w/35' cement

Perforations @ 8901'-8906'

CIBP @ 9055' w/35' cement

Perforations @ 9080'-9083'

CIBP @ 9089' w/35' cement

Perforations @ 9101'-9107'

PBTD 9202' KB

5 1/2" 17#/ft N80TD @ 9225' (KB)

Cement 1st Stage w/200sx Super "C"

Cement 2nd Stage w/1475sx 35:65:6 POZ C

Tail in w/250sx Class "C" (Calc TOC by pressure differential @ 200' from surface)

7 7/8" Hole

**RECEIVED**

OCT 02 2009

**HOBBSOCD**

T/Salt @ 1745'

Yates @ 2180'

San Andres @ 3320'

Abo @ 6920'

Wolfcamp Ls @ 7804'

Penn Clastics @ 8832'

Mississippian @ 9134'