Submit 3 Copies To Appropriate District State of New Mexico	Form C-103	
State of New Mexico Office District I 1625 N. French Dr., Hobbs, NM 88240 District II	WELL API NO.	
District II	30-041-20809	
1301 W. Grand Ave., Artesia, NM 88270 1 9 20 01L CONSERVATION DIVISION	5. Indicate Type of Lease STATE FEE S	
District IV 1000 Rio Brazos Rd., Aztec, NHOBSOCD District IV 1220 South St. Francis D1. Santa Fe, NM 87505	6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name STOLTENBERG	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	8. Well Number 001	
1. Type of Well: Oil Well Gas Well Other	O OCRUPAL 1	
2. Name of Operator SOVEREIGN EAGLE, LLC	9. OGRID Number 263940	
3. Address of Operator P.O. BOX 968, ROSWELL, NM 88202-0968	10. Pool name or Wildcat TULE SAN ANDRES	
4. Well Location		
	and 2310' feet from the FWL line	
Section 26 Township 2S Range 29E	NMPM County ROOSEVELT	
11. Elevation (Show whether DR, RKB, RT, GR		
4394' GL		
Pit or Below-grade Tank Application or Closure	, , ,	
Pit typeDepth to GroundwaterDistance from nearest fresh water well	Distance from nearest surface water	
Pit Liner Thickness: mil Below-Grade Tank: Volume bb	ls; Construction Material	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
	E DRILLING OPNS. □ P AND A □	
	EMENT JOB	
OTHER: OTHER:]	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion		
or recompletion.		
Approved	for plugging of well bore only.	
SEE ATTACHMENT	inder hand to manage at a second	
	(Subsequent Report of Well Plugging) by the found at OCD Web Page under	
Forms, we	w.emnrd.stato.nm.us/ocd.	
,		
· · · · · · · · · · · · · · · · · · ·		
I hereby certify that the information above is true and complete to the best of my know	wledge and helief. I further cortify that any nit or helow	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.		
SIGNATURE TITLE Manager of Op	perations DATE 04/15/10	
Type or print name Frank S. Morgan E-mail address: fmorgan@stratanm.com Telephone No. (575) 622-1127 For State Use Only		
	DATE 4-19-10 1 4-20-10	
Conditions of Approval (if any):	Ch 4-20-10	

SOVEREIGN EAGLE, LLC. TULE FIELD

STOLTENBERG #1 WORKOVER REPORT

SECTION

ROOSEVELT CO, NEW MEXICO

API#

Elevation KB

TD PBTD

2/4/10-	Safety meeting. MI & RU Mayo Marr's. ND wellhead. NU BOP. PU & GI w/ work string. Tag CIBP @ 2809'. Circ. Hole w/ plugging mud. Spot 25 sacks cement. TOH w/ tbg. Dig out wellhead. ND wellhead and weld on pull-nipple. SISD.
2/5/10-	Safety meeting. Repair rig. RU to pull csg. Stretch csg and find free pt @ 2550'. GIH w/ gauge ring. TOH w/ gauge ring. RU & GIH w/ csg cutter. Would not fire. TOH w/ cutter. SISD.
2/6/10-	Safety meeting. RU & GIH w/ 2^{nd} csg cutter. Stuck cutter @ 350'. Pull off tool. GIH w/ tbg. Pound cutter to bottom. TOH w/ tbg. RU & GIH w/ 3^{rd} cutter. Cut csg. @ 2178'. TOH w/ wire-line. Pull 1 jt 4 ½' csg. Lay down. SISD.
2/7/10-	Safety meeting. POH w/ 55 jts 4 ½" csg and lay down. NU BOP. TIH w/ work string to 2228'. Circ. Hole w/ mud. Spot 50 sacks cement @ 2228'. TOH w/ tbg. WOC. SISD.
2/8/10-	Safety meeting. TIH w/ tbg. Did not tag cement. Circ. And spot 50 sack plug @ 2234'. TOH w/ tbg. WOC 5 hrs. TIH w/ tbg. Tag cement @ 2017'. PU and spot 30 sack plug @ 1109'. PU and spot 30 sack plug @ 388'. TOH w/ tbg and WOC. SISD.
2/9/10-	Safety meeting. TIH w/ tbg. Tag @ 274'. Circ. 20 sacks cement from 60' to surface. Set dry-hole mark. Level and clean location.