Submit 3 Copies To Appropriate District	State of New Mexico		Form C-103	
Office District I	Energy, Minerals and Natural Resources		XX/EFF A DE NO.	Revised May 08, 2003
1625 N. French Dr., Hobbs, NM 88240		WELL API NO. 025-36565		
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION		5. Indicate Type of Lease		
District III 1220 South St. Francis Dr.		STATE [FEE 🗹	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505		6. State Oil & G	as Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM			NA	
87505 SUNDRY NOTICE	S AND REPORTS ON WELLS	•	7. Lease Name o	or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			Dan Field	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			•	
1. Type of Well:			8. Well Number	
Oil Well Gas Well Other			1	
2. Name of Operator Mulloy Operating, Inc.			9. OGRID Num	ber
Widiloy Operating, Inc.			225942	
3. Address of Operator 508 West Wall #700, Midland, Texas 79701			10. Pool name o	r Wildcat
4. Well Location				
Unit Letter Q: 1710 feet from the South line and 660 feet from the East line				
Section 1	Township 16 S Ra	ange 34 E	NMPM Lea	County N. Mex
	1. Elevation (Show whether DR 4064 GR			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING				
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI			ILLING OPNS	PLUG AND ABANDONMENT
	MULTIPLE COMPLETION	CASING TEST AI	ND	
OTHER:		OTHER:		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date				
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion				
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Drill 17 1/2" hole to +/-500'. 2. Set and cement 13 3/8" casing. Circulate cement to surface. 3. Drill 12 1/4" hole to +/-4,600'.				
1, Drill 17 1/2" hole to +/-500'.				
2. Set and cement 13 3/8" casing. Circulate cement to surface.				
4. Set and cement 9 5/8" casing . Circulate cement to surface. 5. Drill 7 7/8" hole to +/- 13,000'. Set 5 1/2" casing and cement back to 9 5/8" casing. Utlize DV tool.				
5. Drill / //6 fible to +/- 13,0	00. Set 5 1/2 casing and ce	ment back to 9 5/	o casing. Onize i	1001.
Note, Original C-101 indicate	ed that 8 5/8" wound be run te	o +/- 6.000'. The o	hange was discus	ssed and approved bs
Note. Original C-101 indicated that 8 5/8" wound be run to +/- 6,000'. The change was discussed and approved by Chris Williams on 2-19-04.				
•				15 S. C.
				2: 1. 2. 2. 2.
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE MULL	LOV_TITLE V	ice President		DATE_2/19/04
Type or print name J. W. Mulloy	۵		Telen	hone No. (432) 687-0323
(This space for State use)	h.	·		
9/ , 7	1.1.1	FIELD REPRESENT	ATIVE II/STAFF	MANAGEK
APPPROVED BY Alary W	WMR TITLE	HELD REPRESEN	AUTENT	DATEEB 2 5 2004
Conditions of approval, if any:				· LD ~ J ZUU4