

RECEIVED

JAN 19 2011

HOBBSD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-39683

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Edward State

8. Well Number 11

9. OGRID Number

229137

10. Pool name or Wildcat 44500

Maljamar; Yeso, West

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

COG Operating LLC.

3. Address of Operator

550 W. Texas Ave. Ste. 1300. Midland, Tx 79701

4. Well Location

Unit Letter L : 1650' feet from the South line and 330' feet from the West line

Section 16 Township 17S Range 32E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4040' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/24/10 Test csg to 5200# for 30 min, ok.

11/30/10 Perf Lower Blinebry @ 6550-6750 w/ 1 SPF, 26 holes.

12/2/10 Acidize w/3,500 gals acid. Frac w/112,049 gals gel, 146,562# 16/30 Ottawa sand, 31,062# 16/30 SLC. Set comp plug @ 6510. Perf Middle Blinebry @ 6280-6480 w/1 SPF, 26 holes. Acidize w/3,500 gals acid. Frac w/ 113,851 gals gel, 146,400# 16/30 Ottawa sand, 31,683# 16/30 SLC. Set comp plug @ 6240. Perf Upper Blinebry @ 6010-6210 w/ 1 SPF, 26 holes. Acidize w/3,500 gals acid. Frac w/115,760 gals gel, 147,089# 16/30 Ottawa sand, 31,276# SLC. Set comp plug @ 5640. Perf paddock @ 5490-5610 w/ 1 SPF, 18 holes. Acidize w/ 3000 gals acid. Frac w/ 106,335 gals gel, 110,890# 16/30 Ottawa sand, 17,212# 16/30 Siberprop.

12/7/10 Drill out plugs. Clean out to PBTD 6794.

12/9/10 Set RBP @ 5675. Set pkr @ 5382. Test to 1000#.

12/10/10 Unset pkr.

12/19/10 Perf Paddock @ 5490-5610 w/ 1SPF, 18 holes. Acidize w/ 3000 gals acid. Frac w/ 98,279 gals gel, 99,837# 16/30 Ottawa sand, 21,369# 16/30 Siberprop.

12/21/10 Release RBP. RIH w/206jts 2-7/8" 6.5# J55 tbgs, SN @ 6532.

12/22/10 RIH w/ 2-1/2"x2-1/4"x20' pump. Hang on well.

Spud Date:

11/2/10

Rig Release Date:

11/11/10

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chasity Jackson TITLE Regulatory Analyst DATE 10-22-2010Type or print name Chasity Jackson E-mail address: rodome@conchoresources.com PHONE: 432-685-4385

For State Use Only

APPROVED BY: [Signature] TITLE PETROLEUM ENGINEER DATE FEB 16 2011

Conditions of Approval (if any):