Form 3160-5 (August 2007)

(Instructions on page 2)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT OCD-HOBBS

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 201

5. Lease Serial No. LC 032096(b)

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

			11				
SUBMIT IN TRIPLICATE – Other instructions on page 2.					7. If Unit of CA/Agreement, Name and/or No.		
I. Type of Well							
Oil Well Gas Well Other Injection					8. Well Name and No. East Blinebry Drinkard Unit (EBDU) #018		
2. Name of Operator Apache Corporation					9. API Well No. 30-025-06479		
Ba. Address 3b. Phone No 803 Veterans Airpark Lane, Suite 3000 432/818-100 Midland, TX 79705 432/818-100			(include area code) 2		10. Field and Pool or Exploratory Area Eunice; Bli-Tu-Dr, North (22900)		
4. Location of Well (Footage, Sec., T.,			11. Country or Parish, State				
660' FNL & 330' FEL UL A Sec 11, T21S, R37E					Lea County, NM		
12. CHEC	K THE APPROPRIATE BO	X(ES) TO INDIC	ATE NATURE (OF NOTIC	CE, REPORT OR OTH	IER DATA	
TYPE OF SUBMISSION	IISSION TYPE OF ACT					-	
✓ Notice of Intent	Acidize Alter Casing	Deepen Fracture		_	oduction (Start/Resume)		
Subsequent Report	Casing Repair	Casing Repair New Construction Recomplete			Other Well Repair		
	Change Plans	Plug an	g and Abandon Ten		nporarily Abandon		
Final Abandonment Notice	Final Abandonment Notice Convert to Injection Plug Back			Water Disposal			
Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Refollowing completion of the involved operations. If the operation results in a multiple completion or recompl testing has been completed. Final Abandonment Notices must be filed only after all requirements, including a determined that the site is ready for final inspection.) Apache will be rigging up to repair this well as necessary due to a failed MIT and UIC Violation. **RECEIVED** MAR 2.8 2011* SEE ATTACHED FOR CONDITIONS OF APPROVABBSOCD**					APP MAR /s/ JD BUREAU OF L	l, a Form 3160-4 must be filed o	nce
14. I hereby certify that the foregoing is t	rue and correct. Name (Printe			***	*.50		
Reesa.Holland			Title Sr. Engr T	ech			
Signature Klasa Holland Date 03/03/2011							
• /	THIS SPACE	FOR FEDER	AL OR STA	TE OF	FICE USE	-	
Approved by							
		•	Title			Date	
Conditions of approval, if any, are attache hat the applicant holds legal or equitable entitle the applicant to conduct operations	itle to those rights in the subje	s not warrant or cer cet lease which would	tify			Lino	
Title 18 U.S.C. Section 1001 and Title 43			on knowingly and	willfully t	o make to any departme	ent or agency of the United States as	ay false,
fictitious or fraudulent statements or repre	esentations as to any matter wi	thin its jurisdiction.					

Conditions of Approval

Apache Corporation East Blinebry Drinkard Unit (EBDU) #18

March 24, 2011

- 1. Conduct a Mechanical Integrity Test of the tubing/casing annulus any time the packer or tubing is pulled.
 - a. The test pressure should be 500 psig or at least 200 psig above the tubing (at test time) pressure but no more than 70% of burst of casing test pressure as described by Onshore Order 2.III.B.1.h. (The reservoir pressure may need to be reduced). Trap that pressure and record it on a chart for 30 minutes.
 - b. Less than a 10% leakoff may not restrict injection approval. Any leak-off will be evaluated. Document the MIT on a calibrated recorder chart within 25 to 85 per cent of its full range. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822.
 - c. Submit the recorded MIT chart with a subsequent Sundry Form 3160-5 relating the MIT activity. Include the original and three copies of the recorded chart and Sundry. (the original will be returned to the operator)
- 2. Submit documentation, (NMOCD permit number) of the maximum tubing injection pressure allowed by NMOCD.
 - a. Approved injection pressure compliance is required.
 - Display real time tubing pressure values onsite. A bourdon tube gauge registering 25% to 85% of its full range is acceptable.
 - c. If injection pressure exceeds the maximum approved pressure you will be required to notify the BLM within 24 hours.
 - d. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment.
 - Other unexplained significant variations of rate or pressure will be reported within 5 days of notice.