Form C-103

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED JUL 1948 HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within [illegible] days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

July 6, 1948 — Date

Monument, New Mexico — Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation (Company or Operator) A. Bushing (Lease) Well No. 1 in the SW¼ SW¼ of Sec. 3, T. 11S, R. 32E, N. M. P. M., Wildcat Field, Lea County.

The dates of this work were as follows: July 5,6, 1948

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on July 5, 1948 and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

2985' Total Depth of 6-1/8" hole, Sand and 2882' Total Depth of 8-3/4" hole, Anhydrite. Ran Schlumberger regular survey and their Gamma Ray Survey detailed 2200' - 2400' and 2800' - 2985'. Spotted 10 sx common cement 2985'-2935' at 7:45PM,7-5-48. Displaced with 20 bbls. mud. Spotted 10 sx common cement at top Salt, 1585' - 1560' at 11:00PM and displaced with 10 bbls. mud. Put in top plug in top of surface casing with 10 sx common cement at 3:00AM, 7-6-48 and left 4" pipe 5' high in center of plug.

Witnessed by K. V. Stephenson (Name) Amerada Petroleum Corporation (Company) Foreman (Title)

Subscribed and sworn before me this 6th. day of July 1948

Will Hale Taylor
Notary Public

My commission expires [illegible] MARCH 29, 1952

I hereby swear or affirm that the information given above is true and correct.

Name [illegible]

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

Address Drawer D, Monument, New Mexico

Remarks:

Roy Yarbrough
OIL & GAS INSPECTOR
Name

Title

APPROVED