

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

July 14, 1961

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Socony Mobil Oil Company, Inc.

Santa Fe Pac. "F"

1

I

(Company or Operator)

Well No.

in

(Unit)

NE **SE**
(40-acre Subdivision)

1/4 of Sec.

26

T 9 S

R 36 E

NMPM,

Crossroads

Pool

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 12373'

PBTD: 4980'

Perfs: 10636-10656 & 10622-10632 Squeezed w/50 sks trinity inferno neat, 30 sks below and 20 sks above. 10622-10632 squeezed w/50 sks, 35 sks below and 15 sks above.

Cag: 13 3/8" @ 457' w/450 sks., circulated. 8 5/8" esg. @ 5050' w/2000 sks. 6% Gal. 200 sks. Signalite & 200 sks. neat Trinity Inferno. Circulated. 5 1/2" @ 10762' w/260 sks. Trinity Inferno neat. Top cement @ 9703'.

Propose to shoot & pull 5 1/2" esg. from 9703'. Spot 25 sk. plug @ 9703'. Spot 40 sk. plug @ 9100', cal. fill to 8950'. Spot 25 sk. plug top of Glerietta @ 5575'. Cal. fill to 5482'. Spot 25 sk. plug @ 5050'. Cal. fill to 4955'. Spot 10 sks. cement @ surface and install monument. Mud laden fluid between plugs.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Socony Mobil Oil Company, Inc.

(Company or Operator)

By.....

Senior Clerk

Position.....

Send Communications regarding well to:

Name.....
Socony Mobil Oil Company, Inc.

Address.....
Box 2406, Hobbs, New Mexico