Form C-	10	1
---------	----	---

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

B 4 1949 Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained beto begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such that returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. So instructions in Rules and Regulations of the Commission.

Midland, Texas

Place

Feb. 3, 1949

Date

OIL CONSERVATION COMMISSION. Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as Mid-Continent Petroleum Corp., - U. D. SAWYER "D" One C S C SW/h Well No.

		87	_ 9S	1 Lease Grossroads Lease	
of	Sec.	<u> </u>	., T	, R, N. M., P. M.,Field,	County.
		N		The well is 1980 feet (N.) (S.) of the Kerth line and Section 27-98-36E	feet
				(E.) (W.) of the line of Section 21-92-55	m=
				(Give location from section or other legal subdivision lines. Cross o directions.)	ut wrong
	-	┼┼┝╴╇		If state land the oil and gas lease is No Assignment No	
				If patented land the owner is Crossroads, New Herico	
				Address	
				If government land the permittee is	
				Address	
-1	<u> </u>		- 	The lease is Mid-Continent Petroleum Corporation	
				Address Box 381, Tulsa 2 Okla.	
	A	BEA 640 AC	RES		
L)CATI	WELL CO	BRECTLY	We propose to drill well with drilling equipment as follows: Rotary	

The status of a bond for this well in conformance with Bull 20 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17*	13 3/8	10#	New	250	Cemented	300 (Circ.)
12"	9 5/8	36#	Ħ	4600		3500 *
7 7/8	5 1/2	20#		T. D.		2000 *

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about. [eet

We plan to take this test to approximately 13,000 feet. Additional information: *Production string shall be cemented with 150 per cent of calc. amount to bring cement to the bottom of the 9 5/8" casing. (Approximately 2000 an)

Approved	Sincerely yours,		
except as follows:	Mid-Continent Petroleum Corporation		
	By Haved Sunt		
	PositionDistrict Supt.		
OIL CONSERVATION COMMISSION, By COL WINGROUGH.	Send communications regarding well to Harold Smith.		
A PIL & GAS INSTRUCTION	Box 830. Hidland. Texas		
Title	Address		