


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 065249

Unit YATES



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Yates-Federal

Midland, Texas July 27th, 1950

Well No. 1 is located 1980 ft. from N line and 660 ft. from E line of sec. 31

NE/4, SE/4, Sec. 31
(1/4 Sec. and Sec. No.)

9-S
(Twp.)

36-E
(Range)

N.M. P.M.
(Meridian)

Crossroad-Slaughter
(Field)

Lea
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 4057 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

T.D.- 4952' - 13 3/8" csg. cement @ 356'
9 5/8" csg. " " 4948'
7" " " " 3016' - the 7" csg. put in well a/c
hole in the 9 5/8" csg.

Put 50 sx. cement from bottom up to approx. 4750'.

Shot off & recovered 295' of the 7" csg. and the 9 5/8" csg.

Put in 60 sx. cement from 300' to top.

4" x 4' line pipe monument put on top of hole.

Plugging commenced 6/7/50. Plugging completed 6/12/50.

Company Magnolia Petroleum Co.

Address Box #633

Midland, Texas

By R. T. German
R. T. German
Title Division Supt.