

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions
verse 504)TIE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0359268

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "A"

9. WELL NO.

One (1)

10. FIELD AND POOL, OR WILDCAT

West Crossroads11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec. 31-9S-36E, NMPM**

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1.

OIL
WELL ☐GAS
WELL ☐

OTHER

DRY HOLE

2. NAME OF OPERATOR

MWJ Producing Company

3. ADDRESS OF OPERATOR

413 First Nat'l Bank Bldg., Midland, Texas4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

2310' FNL & 2272' FWL, Section 31, T-9-S, R-36-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4079 RT, 4065 GR*

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

Perforate and TestPULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

Perforating & Testing(NOTE: Report results of multiple completion on Well
Completion or Recore Completion Report and Log form.)REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

May 7, 1964 thru May 20, 1964

Drilled out cement plugs to 10,864'. Perforated 5 1/2" liner as follows:
10,567-78; 10,501-08', 10,276-80'; 9,851-55'; 9,755-59' and 9672-77'.
Tested zones separately with straddle packers. Recovered salt water from all zones.
Spotted cement plugs as follows: 40 sacks from 10,620 to 10,230 and 90 sacks from
9900 to 9140'.

Request permission to plug above perforations and to perforate from ~~8817~~ 8917-27'
and test. This confirms oral approval to plug and test given May 20, 1964.

***Elevations reported on Form 9-331c are incorrect.**

18. I hereby certify that the foregoing is true and correct

SIGNED

Edward H. Jackson

TITLE

V. Pres

DATE

6-12-64

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 16 1964***See Instructions on Reverse Side****GORDON
ACTING DISTRICT ENGINEER****RECEIVED**
JUN 16 1964
U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.