

## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	XX
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico  
PlaceFeb. 21, 1949  
Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the \_\_\_\_\_  
 Skelly Oil Co. U. D. Sawyer Well No. 1 in CNE/4 NE/4  
 Company or Operator Lease  
 of Sec. 33, T. 9S, R. 36E, N. M. P. M., Cross Roads Field.  
 Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION  
 Drilled to total depth of 12,741' encountering salt water which filled 2700' on 5-hr. drill stem test, taken at 12,703'-12,741'. NO OIL OR GAS ENCOUNTERED TO TOTAL DEPTH. Will be plugged in the following manner:

Will run cement plug of 50 sacks, to plug off bottom water, 12,741' to 12,581' then fill hole with heavy mud laden fluid from 12,581' to 12,320', cement plug of 50 sacks 12,320' to 12,160', heavy mud laden fluid 12,160' to 11,450', cement plug of 40 sacks 11,450' to 11,322', heavy mud laden fluid 11,322' to 8000', cement plug of 50 sacks 8000' to 7865', heavy mud laden fluid 7865' to 7200', cement plug of 75 sacks 7200' to 6998', heavy mud laden fluid 6998' to 4800', cement plug of 50 sacks 4800' to 4665', heavy mud laden fluid 4665' to 4000', cement plug of 60 sacks 4000' to 3850' (9-5/8" casing was set at 4602' and cemented to surface) heavy mud laden fluid 3850' to 190', cement plug of 10 sacks 190' to 170', then fill hole to surface with heavy mud laden fluid, install cement cap and 4" marker.

(Confirming oral approval given by Mr. Roy Yarbrough to J. N. Dunlavey, 2/14/49)

Approved \_\_\_\_\_, 19\_\_\_\_  
 except as follows:

Skelly Oil Company

Company or Operator

By

Position

District Superintendent

Send communications regarding well to

Name

Skelly Oil Co.

Address

Drawer "D" Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

*Roy Yarbrough*  
 \_\_\_\_\_