Form C-103

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING OPERA-			
TIONS	REPORT ON RE	PAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL	REPORT ON PUL ALTERING (LING OR OTHER	WISE
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEE	PENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		<u></u>	
	March 1st, 1949		d, Texas.
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO Gentlemen:	Date		Place
Following is a report on the work done and the results of Mid-Continent Petroleum Corporation - U	- 白 現在日本でわ 野白畑	noted above at the Well No	Omo
Company or Operator	Lease		in the
<u>C NE NV</u> of Sec. 34 Crossroads Field,	, T95 Lea	R361	
	ary 21.st		County.
Notice of intention to do the work was (************************************	mitted on Form C 109 on		
T.D. 12750. We ran 12514! of 5 1/2 sacks and 750 sacks. Casing shut of bottom float shoe. We then perform	ff was tested and co ted at 12500 with 1	La two stages 1 ment job leak	ed through
T.D. 12750. We ran 12514 of 5 1/2	" casing, cemented i ff was tested and ce ted at 12504; with)	La two stages 1 ment job leak	ed through
T.D. 12750. We ran 12514! of 5 1/2 sacks and 750 sacks. Casing shut of bottom float shoe. We then perform at 12374 and squeezed with 25 sacks	" casing, cemented i ff was tested and ce ted at 12504; with)	in two stages ment job leak holes, then retested with	ed through
T.D. 12750. We ran 12514! of 5 1/2 sacks and 750 sacks. Casing shut of bottom float shoe. We then perfora at 12374 and squeezed with 25 sacks for 1 hour. Shut Off Tested OK.	" casing, cemented i ff was tested and ce ted at 12504 ' with 1 to 3500#. We then	in two stages ment job leak holes, then retested with	ed through set retainer 2500#
T.D. 12750. We ran 12514: of 5 1/2 sacks and 750 sacks. Casing shut of bottom float shoe. We then perform at 12374 and squeezed with 25 sacks for 1 hour. Shut Off Tested OK.	" casing, cemented i ff was tested and ce ted at 12504! with 1 to 3500%. We then MeVay & Stafford Company I hereby swear or affirm is true and correct.	In two stages a ment job leak holes, then retested with	ed through set retainer 2500# PARTNER Title tion given above
T.D. 12750. We ran 12514: of 5 1/2 sacks and 750 sacks. Casing shut of bottom float shoe. We then perfora at 12374 and squeezed with 25 sacks for 1 hour. Shut Off Tested OK. Witnessed by . J. Stofford Name Subscribed and sworn before me this 1st	" casing, cemented if ff was tested and ce ted at 12504! with 1 to 3500#. We then McJay & Stafford Company I hereby swear or affirm is true and correct. Name	in two stages i ment job leak holes, then i retested with Drilling Co.	ed through set retainer 2500# PARTNER Title tion given above
T.D. 12750. We ran 12514: of 5 1/2 sacks and 750 sacks. Casing shut of bottom float shoe. We then perform at 12374 and squeezed with 25 sacks for 1 hour. Shut Off Tested OK. Witnessed by . J. Stafford Name Subscribed and sworn before me this 1st 	" casing, cemented i ff was tested and ce ted at 12504' with 1 to 3500%. We then MCVay & Stafford Company I hereby swear or affirm is true and correct. Name Position Representing Manual Contents	in two stages i ment job leak holss, then retested with Drilling Co. m that the information drict Supt. ontinent Petro	ed through set retainer 2500# PARTNER Title tion given above
T.D. 12750. We ran 12514: of 51/2 sacks and 750 sacks. Casing shut of bottom float shoe. We then perfora at 12374 and squeezed with 25 sacks for 1 hour. Shut Off Tested OK. Witnessed by . J. Stafford Name Subscribed and sworn before me this 1st day of 19 4	" casing, cemented if ff was tested and ce ted at 12504! with 1 to 3500%. We then MeVay & Stafford Company I hereby swear or affirm is true and correct. Name Position Representing Comp	In two stages i ment job leak holss, then retested with Drilling Co. m that the information that the information the information that the information the information that the information the information that the information the information the information the information that the information the information the information the information that the information the informati	ed through set retainer 2500# PARTNER Title tion given above