NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	ns of the Commission.			uttionai
	Indicate Nature of Report by Ch	ecking Below		
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TO CASING SHUT-OFF	REPOR'	ON ING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETI OPERATION	ON REPOR' (Other)	r on	
1				
	10-20-52		Hobbs, New Me	xico
	(Date)		(Place)	
		o heading noted above at	the	
Following is a report on the wor	k done and the results obtained under tr	le neading noted above as		
Phillips Petroleum Company		Cross		
(Company or C	perator)	(L	tase)	4
	perator) , Well N	in the S	1/4 1/4 of Sec	<u></u> ,
(Contract	or)	_		_
- 100 p 36R NMPM	Wildcat	Pool,		County.
T, R, 14111 1411				
The Dates of this work were as follows:	9-29-52			
Notice of intention to do the work (w	as) (TACCOL) submitted on Form C-102 ((Cross out inco	rrect words)	, 10,
and approval of the proposed plan	mr\ (was not) obtained.			
and approval of the property	(Was not)			
ner	ATLED ACCOUNT OF WORK DONE	AND RESULTS OBTAI	NED	
DETA	ALED ACCOUNT OF WORK DONE	AND RESULTS OBTAI	NED	
DET	AILED ACCOUNT OF WORK DONE			
DET	AILED ACCOUNT OF WORK DONE	0001 to /9351.	Ran 161 joints.	
DET.	ALED ACCOUNT OF WORK DONE K TD. Drilled cement from A	,900' to 4935'.	Ran 161 joints,	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ALED ACCOUNT OF WORK DONE K TD. Drilled cement from A	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920, 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920 , 5-1/2"	ATLED ACCOUNT OF WORK DONE K TD. Drilled cement from A casing set at 4930 . Cemei	900' to 4935'. Ited with 115 sac	Ran 161 joints, ks regular top of cement	
4935 Plug back 4920, 5-1/2" cement. Pumpe at 2845. Tes	ALED ACCOUNT OF WORK DONE The transfer of the	900' to 4935'. Ited with 115 sac Free survey showed O minutes. Test	Ran 161 joints, ks regular top of cement Ok. Foreman	
4935 Plug back 4920, 5-1/2" cement. Pumper at 2845. Tes	TD. Drilled cement from A casing set at 4930. Cement is plug to 4897. Temperate ted casing with 1000 for its case with 1000 for	900' to 4935'. Ited with 115 sac are survey showed 30 minutes. Test	Ran 161 joints, ks regular top of cement Ok.	
4935 Plug back 4920, 5-1/2" cement. Pumper at 2845. Tes	ALED ACCOUNT OF WORK DONE (TD. Drilled cement from A casing set at 4930'. Cement i plug to 4897'. Temperate ted casing with 1000# for (Comp	900' to 4935'. Ited with 115 sac Ire survey showed O minutes. Test	Ran 161 joints, ks regular top of cement Ok. Foreman	
4935 Plug back 4920 , 5-1/2 cement. Pumper at 2845 Tes	TD. Drilled cement from A casing set at 4930'. Cement is plug to 4897'. Temperatived casing with 1000# for its company of the casing with 1000# for its case with 1000# f	oleum Company	Ran 161 joints, ks regular top of cement Ok. Foreman	d comple
4935 Plug back 4920 , 5-1/2 cement. Pumper at 2845 . Tes	ALED ACCOUNT OF WORK DONE (TD. Drilki cement from A casing set at 4930'. Cement i plug to 4897'. Temperate ted casing with 1000# for (Comp	900' to 4935'. Ited with 115 sac Ire survey showed O minutes. Test	Ran 161 joints, ks regular top of cement Ok. Foreman	d comple
4935! Plug back 4920!, 5-1/2" cement. Pumper at 2845!. Tes	TD. Drilled cement from A casing set at 4930'. Cement is plug to 4897'. Temperatived casing with 1000# for its company of the casing with 1000# for its case with 1000# f	oleum Company	Ran 161 joints, ks regular top of cement Ok. Foreman	d comple
4935! Plug back 4920!, 5-1/2" cement. Pumper at 2845!. Tes Witnessed by	ALED ACCOUNT OF WORK DONE ATLED ACCOUNT OF WORK DONE ATLED ACCOUNT OF WORK DONE Casing set at 4930'. Cemer I plug to 4897'. Temperate ted casing with 1000# for The composition of	1900' to 4935'. Ited with 115 sactors survey showed to minutes. Test to the survey showed to minutes. Test to the survey showed to make the survey shows the survey of the best of my knowledge.	Ran 161 joints, ks regular top of cement (Title) nation given above is true an	d comple
4935! Plug back 4920!, 5-1/2" cement. Pumper at 2845!. Tes	TD. Drilled cement from A casing set at 4930'. Cement is plug to 4897'. Temperatured casing with 1000# for the casing with	oleum Company reby certify that the information Dist. Chis	Ran 161 joints, ks regular top of cement (Title) nation given above is true an	
4935! Plug back 4920!, 5-1/2" cement. Pumper at 2845!. Tes Witnessed by	TD. Drilled cement from A casing set at 4930'. Cement is plug to 4897'. Temperatured casing with 1000# for the casing with	oleum Company reby certify that the informate best of my knowledge. Dist. Chis.	Ran 161 joints, ks regular top of cement (Title) nation given above is true an	