

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	XX		

P.O.Box 954; Roswell, N.M.

Dec. 1st. 1937

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Crandall & Osmond and Maxwell Maxwell Permit Well No. 1 in the \_\_\_\_\_  
Company or Operator Lease

SE $\frac{1}{4}$  SE $\frac{1}{4}$  of Sec. 2, T. 11S, R. 36 E, N. M. P. M.,  
Wildcat Field, Lea County

The dates of this work were as follows: Started plugging 21th - completed 29th.

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on Nov. 21st. 1937  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

T.D. 5301 Plugged to 5000 with cement and enough gravel to permit dumping bailer(35sks); fine gravel to 4700'. Halliburton filled hole with heavy mud(12#) Pulled 8" casing to 2840-bottom salt-Halliburton placed 25sks cement across base salt. Pulled 8" out(complete string). Bridged hole at top salt (2360); placed alternate plugs cement and gravel(30sks); then gravel to 1930. Pulled 900' of 10" pipe, leaving about 1450' in hole. Bridged hole at 400', and added fine gravel to mud in hole, after putting 5 sks cement at 360'. Brought gravel and mud to 200'; then 5 sks cement. 40' of 15 $\frac{1}{2}$ " casing remains in hole cemented originally with 40sks cement. Brought mud and gravel to top pipe and set marker of 4" pipe five feet above surface; cemented in with 40 sks cement.

Witnessed by J. Klinger & in part by R. Daugherty; tool pushers for Rowan Drilling  
Name Company Title Company

Subscribed and sworn to before me this 1st

day of December, 1937

Marie Baldy  
Notary Public

My Commission expires Aug 8, 1941

I hereby swear or affirm that the information given above is true and correct.

Name Rodine Crandall

Position Partner and Authorized Agent for Permittee

Representing Crandall & Osmond and Maxwell

2008 Ft. Worth Nat. BK Bldg.

Address Fort Worth, Texas

Remarks:

Above as filed with U.S.G.S. (Roswell)

Name

Title