

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

|   |          |  |  |   |  |
|---|----------|--|--|---|--|
| NOTICE OF INTENTION<br>TO CHANGE PLANS  |          | NOTICE OF INTENTION TO<br>TEMPORARILY ABANDON WELL |  | NOTICE OF INTENTION<br>TO DRILL DEEPER  |  |
| NOTICE OF INTENTION<br>TO PLUG WELL     | <b>X</b> | NOTICE OF INTENTION<br>TO PLUG BACK                |  | NOTICE OF INTENTION<br>TO SET LINER     |  |
| NOTICE OF INTENTION<br>TO SQUEEZE       |          | NOTICE OF INTENTION<br>TO ACIDIZE                  |  | NOTICE OF INTENTION<br>TO SHOOT (Nitro) |  |
| NOTICE OF INTENTION<br>TO GUN PERFORATE |          | NOTICE OF INTENTION<br>(OTHER)                     |  | NOTICE OF INTENTION<br>(OTHER)          |  |

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

March 1, 1956  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the J. S. Slatton

The Ohio Oil Company's

(Company or Operator)

Well No. 1 in P

(Unit)

SE  $\frac{1}{4}$  SE  $\frac{1}{4}$  of Sec. 1, T. 9-S, R. 37-E, NMPM, Wildcat Pool

(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plan to plug and abandon well according to following procedure:

1. Set a 200' cement plug from 11,640' to 11,840'.
2. Set a 200' cement plug from 9400' to 9600'.
3. Set a 200' cement plug from 2800' to 3000'.
4. Set a Model "K" Baker cast iron bridge plug at approx. 2800'.
5. Set a 50' cement plug from 2750' to 2800'.
6. Set a 25' cement plug at surface.
7. Place a 4" pipe marker in top of 9-5/8" casing extending 4' above mean ground level.
8. Mud-laden fluid between all plugs.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

The Ohio Oil Company

ORIGINAL SIGNED BY:

By.....  
CLYDE E. ALTON

Position.....  
Petroleum Engineer

Send Communications regarding well to:

Name.....

Address.....