

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

August 29, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Soco Mobil Oil Company, Inc. **W. R. Bilbrey** Well No. **1** in **D**
(Company or Operator) (Unit)
NW $\frac{1}{4}$ **NW** $\frac{1}{4}$ of Sec. **6**, T. **9 S**, R. **37 E**, NMPM., **Allison Penn.** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 9677'
PB: 9660'
Csg: 10 3/4" @ 407 w/375 sx., 7 5/8" @ 4160 w/1200 sx., 5 1/2" (Liner) 3964-9677 w/870 sx.
Perfs: 9598-9609, 9614-9624

Propose to move in and rig up pulling unit. Pull rods, pump & tubing. Set GI Bridge plug @ 9595' on wire line. Dump Hydromite on top of plug. Perf. 5 1/2" liner in Rough "A" & "B" zones 9543-9550, 9555-9571 & 9573-9582 w/1 Jet SPF (Schlumberger Sonic Log dated 4/7/60). Run tubing & packer, set packer @ 9500 & test. Acidize w/1000 gals 15% HCl Acid, drop 6 RCN Ball Sealers after 500 gals. Re-test. If water is produced set packer between zones @ 9558' and test separately. If well produces oil complete in these zones. If dry or produces water set cement plug above perfs and temporarily abandon well.

Approved....., 19.....
Except as follows:

Soco Mobil Oil Company, Inc.

By **W. R. Bilbrey**
Company or Operator

Position **Group Supervisor**
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Name **Soco Mobil Oil Company, Inc.**
Address **Box 1300, Hobbs, New Mexico**