


\*SUBJECT TO BEI

R. W. STANLEY  
DISTRICT INCH

(SUBMIT IN TRIPLICATE)

HOBBS, and Office

Santa Fe

Lease No.

M 61744

Unit

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

CORRECTION 11-11-60

NOV 14 1960

## SUNDRY NOTICES AND REPORTS ON WELLS

HOBBS, NEW MEXICO.

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas November 11, 1960

Federal ME  
Well No. 1 is located 640 ft. from [N] line and 1300 ft. from [E] line of sec. 8NE 1/4 of NE 1/4 Sec. 8  
(1/4 Sec. and Sec. No.) T-9-S R-37-E  
(Twp.) (Range)

(Meridian)

Midland  
(Field)Law  
(County or Subdivision)New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft. Not run as of this date.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

10-3/4" 240 surface casing will be cemented with 350 sacks, at plus or minus 400'.

7-1/2" 240 Intermediate casing will be cemented with 250 sacks, at plus or minus 4300'.

The well will be drilled to about 5000' to test the Permian zone. The surface in this area is recent alluvium. Drilling will be with rotary and mud. If sufficient shows are encountered, a P.S.T. will be run. If oil is found in commercial quantity - a 4-1/2" casing will be cemented through the pay and gas perforated. A gamma-ray neutron log will be made in any event.

Spud date is set as November 16, 1960.

\* Sufficient cement be used to cover the salt section and all zones of possible pay

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Consolidated Drilling CompanyAddress Box 1639, Midland, TexasBy O. H. Lewis O. H. Lewis  
11-11-60Title Administrative Coordinator