

		X	

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **New Mexico**
Lease No. **LC 067706-C**
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas November 22, 1961

Well No. **King 1** is located **640** ft. from **(N)** line and **640** ft. from **(E)** line of sec. **18**
NW/4 of NE/4 of Sec. 18 T-9-S R-37-E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Allison Pennsylvania **Lee** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **4036** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

A total depth of 9775' was reached Nov. 8, 1961. 9750' of 4-1/2" 11.40 casing was cemented with 200 sacks. Temperature survey located the cement outside this string @ 8300'. The well was logged and perforated Nov. 9. (9600-9700') 4 shots/ft. A dry test was run - no production. 300 gal of mud acid was used - made 1/2 bbl. per hr. oil cut 10%. Acidized w/ 5,000 gal. - after leak was recovered - made 1.20 bbls./hr. cut 10%. Acidized w/ 10,000 gal. Nov. 16th. Stopped 11 bbls. salt water per hr. (Testing 44 hrs.) No show. Great Western Drilling Company plans to set a plug of 25 sacks at 9600', 25 sacks @ 9000', cut and pull 8300' of 4-1/2" and set plugs at 4200' (25 sacks). Then cut 7-1/8" casing @ 1350' and pull. Then place a 25 sack plug at bottom of surface pipe @ 276' and a 10 sack plug at surface.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Great Western Drilling Company**Address **Box 1639, Midland, Texas**By *Officer*Title **Administrative Coordinator**