~`	<u>_</u>		\sim	Budget Bureau No. 42-R358.1. Approval expires 11-30-49.
orm 9-331 a (March 1942)		DLOGICAL SUI	ES INTERIOR RVEY	LAND OFFICE Unit NOV 26 1951 OIL CONSERVATION COMMISSION HOBBS-OFFICE
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE NOTICE OF INTENTION TO TEST WA NOTICE OF INTENTION TO RE-DRILL	PLANS TER SHUT-OFF	SUBSEQU	ENT REPORT OF SHO	TER SHUT-OFF OTING OR ACIDIZING ERING CASING WRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT C NOTICE OF INTENTION TO PULL OR NOTICE OF INTENTION TO ABANDO NOTICE OF INTENTION	R ACIDIZE	SUBSEQU		NDONMENT
NOTICE OF INTENTION TO SHOOT OF NOTICE OF INTENTION TO PULL OF NOTICE OF INTENTION TO ABANDO NOTICE OF INTENTION TO ABANDO INTENTION TO ABANDO (INDIC	ALTER CASING	SUBSEQU SUPPLEM	ENTARY WELL HISTO	RY
NOTICE OF INTENTION TO SHOOT OF NOTICE OF INTENTION TO PULL OF NOTICE OF INTENTION TO ABANDO NOTICE OF INTENTION TO ABANDO (INDICE (INDICE Federal-Carruth Well No	ALTER CASING N WELL PING Bes ATE ABOVE BY CHECK N Docated 1980 ft 98	SUBSEQU SUPPLEM MARK NATURE OF REI	entary well histo FORT, NOTICE, OR OTH and <u>660</u> ft. N. K. P.	Her DATA) (overber 26,, 19_51 from $\left\{ \stackrel{E}{\mathbf{W}} \right\}$ line of sec. 25
NOTICE OF INTENTION TO SHOOT OF NOTICE OF INTENTION TO PULL OR NOTICE OF INTENTION TO ABANDO NOTICE OF INTENTION TO ABANDO (INDICE (INDICE) Well No	ALTER CASING	SUBSEQU SUPPLEM	entary well Histo PORT, NOTICE, OR OTH and <u>660</u> ft.	Her DATA) (overaber 26,, 19.51 from $\left\{ \stackrel{E}{\mathbf{W}} \right\}$ line of sec. 25

ı.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total Depth 12,097' Devonian Lime. Top of Devonian 12,038. On drill stem test from 12,039' to 12,097' recovered 8000' salt water in 30 minutes. Ran Schlumberger electric survey to 12,093'. Will plug back from 12,076' to 11,813' with 100 sacks cement. Will place second cement plug from 5211' to 4948' with 100 sacks cement. Space between plugs will be filled with 9.4 weight mud and viscosity 63. Cement will be allowed to set for 24 hrs., then test with 1000# pressure for 30 minutes. If test is eks will set permanent wire line bridge plug @ 4975'. Perforate 9-5/8" easing from 4914' to 4930' first San Andres some and perforate from 4936' to 4946' second San Andres some.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.				
Company	The Ohie Oil Company			
Address	P. O. Bex 210?			
	Hobbs, New Mexico	By P.B. Clewant		
		Title Superintendent		

U. S. GOVERNMENT PRINTING OFFICE 16-8487-3