## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## **MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Notice of Intention	The state of the s	<del></del>		
O CHANGE PLANS	Notice of Inte Temporarily A		Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	Notice of Inte	иоти	Notice of Intention to Set Liner	
Notice of Intention o Squeeze	Notice of Inte to Acidize	INTION	Notice of Intention to Shoot (Nitro)	
Notice of Intention o Gun Perforate	Notice of Inte (Other)	NTION	Notice of Intention (Other)	
OIL CONSERVATION COMMIS	sion <u>Milland,</u>	Pace)	Pebruary 23, 196	62 M
entlemen:		(1.20)	(56)	ω,
baion Oil Courseny of Ca	alifornie	<u>State</u>	Well No. 3-22	in I
IE	22 <sub>T</sub> 10-5	p 37-E	Vev Underignat	ted D
Drilled 7-7/8" ho:	_	of 12,180 feet	AND REGULATIONS)	
Drilled 7-7/8" hold is proposed to following manner:  Spot 35 sx. cement 1150-1036". Cut of Spot general plans	t plugs from 12,16 off and recover as	of 12,180 feet sell on or above 30-12,056*, 980 pproximately 13	and regulations)  t.  ut February 21, 1962 in  00-9686', 6000-5886', 6  192' of 8-5/8" casing.  1150'. 25 sx. plug 675	and -575°, and
Drilled 7-7/8" holdering manner:  Spot 35 sx. cement 4150-4036'. Cut of Spot cement plugs 10 sx. plug in top in top of 11-3/4"	t plugs from 12,18 off and recover as so follows: 35 a p of 11-3/4" surface casing.	of 12,180 feet sell on or above 30-12,056*, 980 pproximately 13	and regulations)  t.  ut February 21, 1962 in  00-9686', 6000-5886', 6  192' of 8-5/8" casing.	and -575°, and e cenented
Drilled 7-7/8" hold in the proposed to following manner:  Spot 35 sx. cement 4150-4036'. Cut of Spot cement plugs 10 sx. plug in to	t plugs from 12,18 off and recover as so follows: 35 a p of 11-3/4" surface casing.	of 12,180 feet sell on or about 10-12,056', 980 proximately 1220-1200 casing. A	and regulations)  t.  ut February 21, 1962 in  00-9686', 6000-5886', 6  192' of 8-5/8" casing.  1150', 25 sx. plug 575.  4" marker pips will be  1 Company of California	and -575°, and e cenented
Drilled 7-7/8" hold is proposed to following manner:  Spot 35 sx. cement 4150-4036'. Cut of Spot cement plugs 10 sx. plug in top of 11-3/4"	t plugs from 12, 16 off and recover as as follows: 35 a p of 11-3/4" surface casing.	of 12,180 feet sell on or about the control of 12,056°, 980 peroximately like, plug 1220-lace chains. A position. Description.	and regulations)  t.  ut February 21, 1962 in  00-9686', 6000-5886', 6  192' of 8-5/8" casing.  1150', 25 ex. plug 675.  4" marker pips will be	and -575°, and e committed

Ala Karb Tara Arawa

Mailand. Terren