

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/2/62)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

HOBBS DISTRICT O.C.C.
JUN 30 10 05 AM '64

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

June 29, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation State **E "B"** Well No. **2** in **C**
(Company or Operator) Lease (Unit)
NE $\frac{1}{4}$ **NW** $\frac{1}{4}$ of Sec. **27**, T. **10S**, R. **37E**, NMPM, **North Echols Devonian** Pool
(40-acre Subdivision) Lea
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plan to P&A well as follows: Spot 25 sack cement plug at base of 5-1/2" casing at 11,875'. Cut 5-1/2" at approx. top of cement which is at 10,100'. Spot 25 sack cement plugs at - in and out top 5-1/2" casing cut, at 9300', 8800', 7770', 6300', 5716'. Cut 8-5/8" casing at approx. top of cement which is at 1818'. Spot 25 sack cement plugs at - in and out top 8-5/8" casing cut, and base 13-3/8" casing at 338'. Spot 10 sack plug at surface. Mud will be between plugs.

NOTE: As per Form C-102 dated 5-18-64, logs were run in well. Logs did not show any zones of porosity.

Approved....., 19.....
Except as follows:

Amerada Petroleum Corporation
Company or Operator

By *D.C. Cap...*

Position **District Superintendent**
Send Communications regarding well to:

Approved *4270*
OIL CONSERVATION COMMISSION

By *John R. ...*

Name **Amerada Petroleum Corporation**

Title *SUPERVISOR DISTRICT*

Address **Box 668 - Hobbs, New Mexico**