

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

March 12, 1955

(Date)

Tatum, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

(Company or Operator)

State EUB

(Lease)

McVay and Stafford Drilling Company

(Contractor)

Well No. 2 in the NE 1/4 NW 1/4 of Sec. 27

T. 10-S, R. 37-E, NMPM., North Echel Pool, Lea County.

The Dates of this work were as follows: 3-12-55

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____,

(Cross out incorrect words)

and approval of the proposed plan (~~was~~) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11,901' Total Depth. Limb. Finished drilling 7-7/8" hole @ 11,901' at 3:45 AM, 3-12-55. Ran Schlumberger surveys. Ran 290 joints of 5-1/2" OD casing set @ 11,875' and cemented with 500 sacks cement. Plug down to 11,790' @ 1:05 AM 3-15-55. Maximum pump pressure - 1600#. Ran temperature survey and found top of cement outside of 5-1/2" OD casing @ 10,100' or 51.6% fill. After W.O.C. for 24 hours - tested 5-1/2" OD casing with 1200# for 1/2 hour before drilling cement plug - no pressure drop. Drilled cement plug from 11,790' to 11,875' and 7' of cement below shoe, washed to bottom and tested 5-1/2" OD casing with 1200# for 1/2 hour - no pressure drop. Continued with completion operations.

Witnessed by I. W. Wiseman
(Name)

Amerada Petroleum Corporation
(Company)

Foreman
(Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *[Signature]*
Position: Assistant District Superintendent

Representing Amerada Petroleum Corporation
Address: Russell Star Route Tatum, New Mexico

(Title)

(Date)