

C.W. TRANE

MORSE "A" #1
660' FNL + 660' FEL
Sec. 28-T10S-R27E
Lea County, N.MEX

CURRENT Wellbore Diagram.
As of 10-15-91

5 1/8" Csg TESTED TO 3000' +
AFTER ALL REPAIRS

2 7/8" N-80 Tbg.

w/ 2 7/8" Big Bore X 5/8"
LOX-Set PKR w/
2.25" F-HIPPS IN
on/off TOOL.

PKR SET @ 11,750'

Perforate 11806-10
w/ 4" C.F.

Perfs 11905-30
Squeeze w/ 150SX
CLASS H

13 3/8 48" @ 343
Cement w/ 400SX
CIRCULATED.

8 5/8 30" @ 4250
Cement w/ 250SX
CIRCULATED.

5 1/2" 15.50" R-55
Csg Tie in @ 5104'
Cement w/ 250SX "H" LITE +
200SX "H" NEAT
Circ. to Surface

Cement w/ 150SX "H" NEAT
Squeeze to 2600'

Cement w/ 275SX "H" + 720 CFH
Squeeze to 1600'

Cement w/ 175SX CLASS "H"
+ 720 CFH
Squeeze w/ 1800'

Cement w/ 70 SX CLASS "H"
Squeeze to 3600'

Cement w/ 264 CLASS "H"

700 @ 10248'

5 1/2" 1740" N-80 Csg @ 11,987'
Cement w/ 350SX "H"

Exhibit A

RECEIVED

NOV 14 1991

U.S. DEPARTMENT OF
ENERGY