

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, (result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<input checked="" type="checkbox"/>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

May 16, 1953
(Date)

Tatum, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation
(Company or Operator)

State FFA

(Lease)

Noble Drilling Corporation
(Contractor)

Well No. 1 in the 660' From East Line 3

2280' From South Line

T11-S, R. 37-E, NMPM, Rehob - Devonian Pool, Lea County.

The Dates of this work were as follows: May 15, 1953

Notice of intention to do the work (was) (was not) submitted on Form C-102 on May 15, 1953, 19

and approval of the proposed plan (was) (was not) obtained. (Note: Section 3 is a short section - 3253.8' from North to South on East Boundary)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11,685' - Total Depth. Line. Ran Schlumberger surveys. Spotted a 35 sack cement plug from 9950' to 9836'; a 35 sack cement plug from 4287' to 4175'; and ran McCullough jet type casing cutter and cut 8-5/8" OD casing off @ 1634' - pulled a total of 40 joints for 1630'. Spotted a 15 sack plug of cement from 319' to 337' and a 10 sack cement plug from 0 to 10' in top of 13-3/8" OD casing. Hole was filled with heavy drilling mud between all cement plugs. A piece of 4" line pipe was cemented in top of 13-3/8" OD casing and extends 5' above ground level to serve as a abandoned well marker.

(Drilling of 7-7/8" hole to Total Depth of 11,685' was completed @ 10:00 PM on May 13, 1953)

Witnessed by R. J. Brakey Amerada Petroleum Corporation Farm Boss
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

J. J. Stanley
(Name)
Eng.
(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Edwin W. H. Wiseman

Position: Foreman

Representing: Amerada Petroleum Corporation

Address: Roswell Star Route Tatum, New Mex.