

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-5283	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
-----------------------------------	--	--------------------------------

Name of Operator
Yates Petroleum Corporation

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER A 660 FEET FROM THE North LINE AND 658 FEET FROM

THE East LINE, SECTION 12 TOWNSHIP 11S RANGE 37E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3934' GR

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
WELL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>

REMEDIAL WORK	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>
CASING TEST AND CEMENT JOBS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

ALTERING CASING	<input type="checkbox"/>
PLUG AND ABANDONMENT	<input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11862' - Ran packer & seating nipple on 344 jts of 2-7/8" tubing. Set packer at 10684'. Treated perforations w/2500 gals 15% NE acid w/inhibitor. Swab tested perfs 10716-40'. WIH w/Hollow Steel Carrier gun on wireline at 9679-9730' w/37 .50" holes as follows: 9679-83' (5 holes) & 9698-9730' (32 holes). Pumped 1000 gals of 15% NE acid to spot over perfs. Pulled packer above perforations. Set at 9633'. Swabbed load water back. Testing well.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CHECKED [Signature] TITLE Engineering Secretary DATE 5-20-81

APPROVED BY [Signature] TITLE [Signature] DATE May 2, 1981

CONDITIONS OF APPROVAL, IF ANY: