

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name <i>Taylor 17/2</i>
9. Well No. <i>1</i>
10. Field and Pool, or Wildcat <i>Undersaturated</i>
12. County <i>Lea</i>

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <i>bed-entry dry hole</i>
2. Name of Operator <i>Tennessee Oil Company</i>
3. Address of Operator <i>Box 1031 Michland, Texas 79701</i>
4. Location of Well UNIT LETTER <i>IT</i> . <i>1650</i> FEET FROM THE <i>South</i> LINE AND <i>1980</i> FEET FROM THE <i>East</i> LINE, SECTION <i>25</i> TOWNSHIP <i>11-S</i> RANGE <i>37-E</i> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) <i>3904 RB</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to plug & abandon well as follows:
Circulate and wash then hole for plugging. Set cement
plug of Class "H" cement as follows: #1 - 50 sds F/9882'
to 9730'; #2 - 25 sds F/7600' to 7524'; #3 - 25 sds F/
5500' to 5424'; #4 - 35 sds F/4400' to 4294. End
dry hole marked and clean area.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *W. L. Hatfield* TITLE *Production Clerk* DATE *4-23-70*
APPROVED BY *[Signature]* TITLE *SUPERVISOR DISTRICT* DATE *APR 27 1970*
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 24 1970

OIL CONSERVATION COMM.
HOBBBS, W. H.