

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(Other, Instr
verse side)

50-025-01037
Form approved
Budget Bureau No. 100-1
Expires August 31, 1989

5. LEASE DESIGNATION AND SERIAL

NM-83628

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sawyer Federal

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

Sawyer Devonian

11. SEC., T., R., M., OR BLE. AND
SUBVY OR AREA

Sec. 7, T9S, R38E

12. COUNTY OR PARISH 13. STATE

Lea

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

C. W. Trainer

3. ADDRESS OF OPERATOR

c/o Oil Reports & Gas Services, Inc. Box 755, Hobbs, NM 88241

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below)
At surface

1980' FSL & 660' FWL of Sec. 7 unit L

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3987 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANT

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill surface plug 3/20/90. Tag top of 7 5/8" liner at 4015. Drill cement plugs & circulate hole clean to top of 5 1/2" casing stub. Ran 5 1/2" 15.5# J-55 casing & spliced together at 5753. Cemented with 575 sacks Pacesetter Lite with 1/4# celloseal per sack, 2% calcium chloride & tailed in with 250 sacks class "C" with 5# gilsonite per sack, 6% CF-1 and 5% KCL. Plug down 11:40 AM 4/4/90. Circulated 35 sacks. WOC 21 hours. Tested casing & BOP to 3000# for 30 minutes, test O.K. Start drilling cement 9:00 AM 4/5/90.

ACCEPTED FOR RECORD

Ar

APR 26 1990

18. I hereby certify that the foregoing is true and correct

CARLSBAD, NEW MEXICO

SIGNED

William L. Hall

TITLE

Agent

DATE 4/9/90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side