

Form 9-331a  
(March 1942)

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces  
Lease No. 080008  
Unit L

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

|   |                                     |   |  |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL.....                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |  |
| NOTICE OF INTENTION TO CHANGE PLANS.....            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     |                                     | SUBSEQUENT REPORT OF ALTERING CASING.....       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... |                                     | SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....  |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        |                                     | SUBSEQUENT REPORT OF ABANDONMENT.....           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    |                                     | SUPPLEMENTARY WELL HISTORY.....                 |  |
| NOTICE OF INTENTION TO ABANDON WELL.....            |                                     |   |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

*Simmons*  
Federal-~~Hydr~~  
Well No. 1 is located 1900 ft. from N line and 600 ft. from E line of sec. 7  
N 1/2 of N 1/2 7 (1/4 Sec. and Sec. No.) 9-5 (Twp.) 38-E (Range) N.M.P.M. (Meridian)  
Wilcox (Field) Lee (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft. will be supplied later.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Plan to drill this well into the Devonian at approximately 12,700 feet.

CASING PROGRAM-

300' of 13-5/8" O.D. spiral Weld 36# casing and cement back to surface.  
4300' of 8-5/8" O.D. 28# 432# H-40 & J-55 casing and cement with 2000 sacks.  
Will run 7" OD or 8-1/2" OD casing and set on top of the pay and cement with 600 sacks.

We propose to drill into the Devonian unless oil in sufficient quantity is discovered at a lesser depth.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Harmon Petroleum Corporation - Oil Division

Address Drawer H

Seminole, Texas

By F. H. Wolfe

Title Division Manager