

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

L.C. 068035

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Landreth-Federal

9. WELL NO.

1

10. FIELD AND-POOL, OR WILDCAT

Sawyer San Andres Gas

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 18, T9S, R38E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. NAME OF OPERATOR Ralph S. Cooley	
3. ADDRESS OF OPERATOR P. O. Box 254, Midland, Texas	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660 feet from North line and 1980 feet from West line, Section 18, Township 9 South, Range 38 East	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3976 GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spotted cement plug with tubing from 4700' to total depth of 4985'.
2. Loaded hole with 11 pound 60 viscosity mud.
3. Shot off 5-1/2" casing at 1300'. Recovered 1300 feet of 5-1/2" casing.
4. Spotted cement plug with tubing 1200 feet to 1400 feet across stub of 5-1/2" casing.
5. Spotted 100 feet of cement across the 13-3/8" surface casing seat.
6. Spotted 50 feet of cement (0 to 50 feet) in top of 13-3/8" surface casing.
7. Erected regulation marker.
8. Cleaned up and graded location. Filled in Burn pit. Ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Operator

DATE February 4, 1966

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

APPROVED

JUN 1 1966

J. L. GORDON  
ACTING DISTRICT ENGINEER

XERO COPY

XERO COPY

XERO COPY

XERO COPY