

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-065151

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brown Federal "51"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Sawyer San Andres

11. SEC. T., R., M., OR B&K. AND
SURVEY OR AREA

Sec. 19, T9S, R38E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

M G M Minerals

3. ADDRESS OF OPERATOR c/o Oil Reports & Gas Services, Inc.
P. O. Box 763, Hobbs, New Mexico 882404. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FWL & 585' FWL of Section 19

NOV 9 1976

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3967' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Re-entry & Run Casing ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Start Re-entry 10/23/76: Install BOP & pick up 7 7/8" bit. Drill out top plug @ 11:00 AM. Test BOP to 600# O.K. Clean out to top of 7" cut off at 1200'. Condition mud & hole.
2. Put on 6 1/8" bit, enter 7" casing and clean out to 4868' to top of bottom plug. Drill cement to 4969' GL.
3. Run 123 jts 4 1/2" 9.5# J55 with guide shoe & float collar. Bottom 120' with Ruf-Cote & 320' with centralizers. Cement @ 4969 with 110 sacks Class H with 0.5% CFR-2 & 8# salt per sack. Plug down 4:15 AM with 1100# 10/27/76.
4. Temp Survey in 8 hours. Top cement 4500'

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

11/8/76

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

NOV 10 1976

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Section 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State Federal office for specific instructions.

Section 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485

