	udget Bureau No. 42-R368.4. proval expires 12-31-60.
Form 9-331 a (Feb. 1951)	(SUBMIT IN TRIPLICATE)
•	UNITED STATES

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING.
(This well was formerly Warren Petroleum #1 Federal Border	$\frac{0 \text{ ctober } 21}{\text{St}}$ line and 1980 ft. from $\begin{bmatrix} \mathbf{E} \\ \mathbf{M} \end{bmatrix}$ line of sec. 20
SW/4 NE/4 Sec. 20 9S (X Bec. and Bec. No.) (Twp.) ( Sawyer (San Andres-Gas) (County of	38ENMPNRange)(Meridian)LeaNew Mexicor Subdivision)(State or Territory)

The elevation of the derrick floor above sea level is 3963... ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Propose to re-enter the Warren Petroleum #1 Federal Border Unit Well with Cible Tools and clean out to 5050'. (Present T.D. 9500') Run 4 1/2" dasing to 5050' cemented with 100 sacks. Clean out to 5020' and mani-Ray-Neutron collar logs from 5020' to 4520'. Perfor te from log approximately 30' total within the interval from 4970' to 4980' with four let shots per toot. Run 2" cubing with treating packer. Treat all perforations with 500 gallons mud acid. Swab dry and test. Treat all perforations with 500 gallons regular acid. Swab dry and test. Pull tubing and packer and rerun tubing with no packer for completion tests.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Alamo Corporation

Address 2010 34th Street

Lubbock, Texas


By Lloyd Henderson

Title Geologist