



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 43-RM.4
Approval expires 12-31-60.

Land Office of the O. C. C.
LC-067775, LA-087762
L...
U-...

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... <input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 9, 1963

No. 1 D.G. McCormick

Well No. is located 1980 ft. from $\left. \begin{matrix} N \\ S \end{matrix} \right\}$ line and 660 ft. from $\left. \begin{matrix} E \\ W \end{matrix} \right\}$ line of sec. 29

SW/4 NW/4 of Sec. 29 9S 38E NMPM
(1/4 Sec. and 1/4 Sec. No.) (Twp.) (Range) (Meridian)

Sanger (Field) Lea (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3956 ft. (K.B.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

(All measurements from Kelly bushings elevation 3956'). Moved in pulling unit. Pulled tubing and packer. Ran tubing with retrievable bridge plug set at 4999'. Sand-jet with four holes per plane at 4912', 4918', 4922', and 4925'. Treated with 10,000 gallons of gelled 15% acid and 10 ball sealers; breakdown pressure: 2700#; maximum: 3000#; minimum: 2500#; displacement: 3300#; instant shutdown: 1850#; after 5 min.: 1590#; flushed with crude oil. Swabbed well in; 70 hour blow-down; 1,200 mcfd thru 20/64" choke, flowing tubing pressure: 580#. Killed zone with crude, retrieved bridge plug and tubing. Re-ran open-ended tubing to 4903'. Swabbed well in; presently flowing load. Will produce from perforations 4968' to 4912', 4925', 4922', 4818' and 4912'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Alamo Corporation

Address 2010 34th Street

Lubbock, Texas

By Lloyd Henderson

Title Geologist