

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Dyco Petroleum

3. ADDRESS OF OPERATOR

420 NBT Bldg., 320 S. Boston, Tulsa, OK 73104

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 990' F&B & 990' FEL Sec. 31-T9S-R38E

AT SURFACE: Unit P

AT TOP PROD. INTERVAL: SAAB

AT TOTAL DEPTH: SAAB

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☒

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

LC-063623

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Federal

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Union Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Sawyer

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T9S, R38E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

LC 063623

15. ELEVATIONS (SHOW DF, KDB, AND WD)

KB - 3950' WD - 5007'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

MAY 2 1983

OIL & GAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

ROSWELL, NEW MEXICO

- 1) Set CIBP @ 4,900'. Cap bridge plug with 35' cement using dump bailer.
- 2) Determine free point of casing and cut casing above free point.
- 3) Spot 100' cement plug across cut (50' in and out of cut).
- 4) Pull casing to 2,250' and spot 100' cement plug from 2,150-2,250' (at top of salt).
- 5) Pull casing to 425' and spot 100' cement plug from 325-425' (50' in & out of surface casing).
- 6) Pull remainder of casing out of hole and spot 50' surface cement plug.
- 7) Weld cap and mark well as per regulations.
- 8) Clean and restore location to original condition or as per field inspectors requests.

Estimated start date: Upon approval.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Engineer DATE April 28, 1983

APPROVED

(This space for Federal or State office use)

APPROVED BY S. J. PETER W. CHESTER TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

MAY 6 1983