Form	C-101
------	-------

ANTOO N	OTT	COMORD	TT A MITON	CON	OCTON
SXICO	1) 11 1.	CUNSER	VATION	UUUW.	- 551UN

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instruction in Rules and Regulations of the Commission.

	Fort Worth, Texas	October 27, 1944
OIL CONSERVATION COMMIS Santa Fe, New Mexico.	Place Place	Date
Gentlemen:		
Drilling Co.	s our intention to commence the drilling of a well Simmons Federal Permit Well No.	L in Center of SE/4 of
of Sec. 18, T-10-8, R.	-38-E, N. M. P. M., Wilders Field,	Lea County
Ν.	The well isfeet (N.)	he <b>S</b> line and <b>660</b> feet
	(W.) of the <u>I</u> line of <u>Sec. 18</u> (Give location from section or other legal subdivision If state land the oil and gas lease is No If patented land the owner is Address If government land the permittee is <u>Simmer</u> Address The lessee is <u>Rowan Drilling Comp</u>	on lines. Cross out wrong directions) Assignment No. Ons Federal Permit
AREA 640 ACRES	Address 903 Commercial Std. Bldg	g. Fort Worth, Texas
LOCATE WELL CORRECTLY	We propose to drill well with drilling equipment a	as follows: Rotary tools

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: **Permanent bond on file** 

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17"	13-3/8* 0D	48 lb. H-40	2nd hand	200*	cemented	300 sx
11"	8-5/8" OD	32 lb. J-55	Иен	4200*	cemented	1000 sx

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil and gas sand should occur at a depth of about 5050 feet.

Additional information: It is proposed to use two stage cement job on 8-5/8" O.D. casing using 300 sacks at bottom of hole and 700 sacks at top of Anhydrite at approximately 2300 ft.

Approved, 19	Sincerely yours,		
except as follows:	ROWAN DRILLING COMPANY Company or Operator		
	By A.C. allen		
	Position Geologist		
OIL CONSERVATION COMMISSION	Send communications regarding well to		
By	Name ROWAN DRILLING COMPANY		
	903 Commercial Standard Bldg.		
Title	Address Fort Worth. 2. Texas		

## 

٠ •

 $\phi = e^{-i\omega t}$  , we define the constraint of the two states of the constraint of t

•

 $(1,1) \in \mathbb{R}^{n} \times \mathbb{R}^{n} \to \mathbb{R}^{n}$  , the set of the decomposition

the contract of the second s