

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in **TRIPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

June 29, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Amerada Petroleum Corporation State E "C" Well No. 1 in B
(Company or Operator) (Unit)
NW 1/4 NE 1/4 of Sec. 16, T. 11S, R. 38E, NMPM, East Echols Devonian Pool
(40-acre Subdivision)
County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Well is no longer economical to produce. Plan to P&A as follows: Spot 25 sack cement plug at 5-1/2" casing perfs. of 12,021'. Cut 5-1/2" casing above top of cement which is at 9860'. Spot 25 sack cement plug in and out top of 5-1/2" casing cut. Spot 25 sack cement plugs at 7800', 6500', 6000' and in and out bottom of 8-5/8" casing at 4452'. Cut 8-5/8" casing above top of cement which is at 2481'. Spot 25 sack cement plugs in and out top of 8-5/8" casing cut, at 2500' and in and out bottom of 13-3/8" casing at 339'. Spot 10 sack cement plug at surface. Mud will be between plugs.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By

Title

Amerada Petroleum Corporation
Company or Operator

By

Position

District Superintendent

Send Communications regarding well to:

Name

Amerada Petroleum Corporation

Address

Box 668 - Hobbs, New Mexico