

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in OUINTUPLICATE.

	Petrolem	a Corporati	Lon	• • • • • • • • • • • • • • • • • • • •	***************************************	State E "C		
	(Cc	ompany or Operator)				11-8	B 38-E	NMP
l No	• • • • • •	, in ¹ ⁄ ₄	of ¹ /4	4, of Sec	, 1 •	,	, R	, IVMI
	designates	1		Pool,	1040		To ob	Cour
	90	feet from	Jeren	line and	1700	feet fron	1	
Section	16	If State	Land the Oil and	d Gas Lease No.	is			
lling Com	menced	terch 4, 19	57 , 1	19 Drilling	was Completed	June 5,		19
ne of Dri	lling Contractor	Noble D	rilling Cor	peration				•••••
dress 3	21 Stamel	ind Building	r - Tulse,	Oklahema	-			
	ve sen level at	Top of Tubing He	ad 39141 D) .F.	The inf	ormation given	is to be kep	t confidential u
		,						
				SANDS OR ZO				
. 1, from		to						
. 2, from	2, fromto			No. 5, from			to	
. 3, from		to		No. 6	, from		to	
				TANT WATER				
clude data	on rate of wat	er inflow and elev	vation to which	water rose in noi	. ,	foot		
. 1, from			to		***************************************	lcct		•••••
. 2, from			to	·····	••••	eet	• • • • • • • • • • • • • • • • • • • •	
. 3. from								
. 4, from.			to		,	feet		
size	WEIGHT PER FOO	NEW OR	to	CASING RECO	······································	feet		PURPOSE
o. 4, from	WEIGHT PER FOO	NEW OR	AMOUNT 320t	CASING RECO KIND OF SHOE Guide	RD CUT AND	feet. ,		
size	WEIGHT PER FOO	NEW OR USED	AMOUNT 320t 4432t	CASING RECO KIND OF SHOE Guide Guide	RD CUT AND	feet. ,		
size	WEIGHT PER FOO	NEW OR USED	AMOUNT 320t	CASING RECO KIND OF SHOE Guide	RD CUT AND	feet. ,		
size	WEIGHT PER FOO	NEW OR USED	AMOUNT 320t 4432t	CASING RECO KIND OF SHOE Guide Guide	RD CUT AND	feet. ,		
size	WEIGHT PER FOO	NEW OR USED	AMOUNT 3201 44321 120931	CASING RECO KIND OF SHOE Guide Guide	CUT AND PULLED FROM	feet. ,	ONS	PURPOSE
size 3-3/8* 8-5/8* 5-1/2*	WEIGHT PER FOO	NEW OR USED	AMOUNT 3201 44321 120931	CASING RECO KIND OF SHOE Guide Guide Float	CUT AND PULLED FROM	feet. ,	ONS	
size 3-3/8* 8-5/8* 5-1/2*	WEIGHT PER FOO	NEW OR USED New New New New New New	AMOUNT 320t 4432t 12093t MUDDING NO. SACKS OF CEMENT	CASING RECO KIND OF SHOE Guide Guide Float AND CEMENT METHOD USED	CUT AND PULLED FROM	PERFORATI	ONS	PURPOSE MOUNT OF
size 3-3/8* 8-5/8* 5-1/2*	WEIGHT PER FOO	NEW OR USED NOW INCLUDED NOW INCLUDED WHERE	AMOUNT 320t 4432t 12093t MUDDING NO. SACKS OF CEMENT 275	CASING RECO RIND OF SHOE Guide Guide Float AND CEMENT	CUT AND PULLED FROM	PERFORATI	ONS	PURPOSE MOUNT OF
size 3-3/8* 8-5/8* 5-1/2*	WEIGHT PER FOO 344 324 17-205 SIZE OF CASING 13-3/8*	NEW OR USED New New New New New New New New New Ne	AMOUNT 320t 4432t 12093t MUDDING NO. SACKS OF CEMENT 275	CASING RECO KIND OF SHOE Guide Guide Float AND CEMENT METHOD USED	CUT AND PULLED FROM	PERFORATI	ONS	PURPOSE MOUNT OF
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE	WEIGHT PER FOO 344 324 17-205 SIZE OF CASING 13-3/8*	WHERE SET 3391 426214452	AMOUNT 320† 4432† 12093† MUDDING NO. SACKS OF CEMENT 275 88	CASING RECO RIND OF SHOE Guide Guide Tlost AND CEMENT METHOD USED Halliburte	CUT AND PULLED FROM	PERFORATI MUD GRAVITY	ONS	PURPOSE MOUNT OF
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE	WEIGHT PER FOO 344 324 17-205 SIZE OF CASING 13-3/8*	NEW OR USED New OR	AMOUNT 320† 4432† 12093† MUDDING NO. SACKS OF CEMENT 275 xx 1 1500 * 500 **	CASING RECO RIND OF SHOE Guide Guide Guide Tlost AND CEMENT METHOD USED Halliburte PRODUCTION	CUT AND PULLED FROM TING RECORD	PERFORATI MUD GRAVITY	ONS AAM	PURPOSE MOUNT OF
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE 7-1/2* 1* 7-7/8*	WEIGHT PER FOO 344 324 17-205 17-205 13-3/8* 4-5/8* 5-1/2*	WHERE SET 3391 40614452 121101	AMOUNT 320 4432 12093 MUDDING NO. SACKS OF CEMENT 275 1500 RECORD OF 1	CASING RECO KIND OF SHOE Guide Guide Float AND CEMENT METHOD USED Helliberta PRODUCTION o. of Qts. or Ga	CUT AND PULLED FROM TING RECORD AND STIMULA als. used, interval	PERFORATI MUD GRAVITY TION treated or sho	ONS AMM	PURPOSE MOUNT OF TUD USED
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE 7-1/2* 1* 7-7/8*	WEIGHT PER FOO 344 324 17-205 17-205 13-3/8* 4-5/8* 5-1/2*	NEW OR USED New OR	AMOUNT 320 4432 12093 MUDDING NO. SACKS OF CEMENT 275 1500 RECORD OF 1	CASING RECO KIND OF SHOE Guide Guide Float AND CEMENT METHOD USED Helliberta PRODUCTION o. of Qts. or Ga	CUT AND PULLED FROM TING RECORD AND STIMULA als. used, interval	PERFORATI MUD GRAVITY TION treated or sho	ONS AMM	PURPOSE MOUNT OF TUD USED
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE 7-1/2* 1* 7-7/8*	WEIGHT PER FOOT 364 324 17-204 SIZE OF CASING 13-3/8* 5-1/2* 12-1/2*	WHERE SET 3391 40614452 121101	AMOUNT 320 4432 12093 MUDDING NO. SACKS OF CEMENT 275 1500 RECORD OF 1	CASING RECO KIND OF SHOE Guide Guide Float AND CEMENT METHOD USED Helliberta PRODUCTION o. of Qts. or Ga	CUT AND PULLED FROM TING RECORD AND STIMULA als. used, interval	PERFORATI MUD GRAVITY TION treated or sho	ONS AMM	PURPOSE MOUNT OF MUD USED
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE 7-1/2* 1* 7-7/8*	WEIGHT PER FOOT 364 324 17-204 SIZE OF CASING 13-3/8* 5-1/2* 12-1/2*	WHERE SET 3391 40614452 121101	AMOUNT 320 4432 12093 MUDDING NO. SACKS OF CEMENT 275 1500 RECORD OF 1	CASING RECO KIND OF SHOE Guide Guide Float AND CEMENT METHOD USED Helliberta PRODUCTION o. of Qts. or Ga	CUT AND PULLED FROM TING RECORD AND STIMULA als. used, interval	PERFORATI MUD GRAVITY TION treated or sho	ONS AMM	PURPOSE MOUNT OF TUD USED
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE 7-1/2* 1* 7-7/8*	WEIGHT PER FOOT 364 324 17-204 SIZE OF CASING 13-3/8* 5-1/2* 12-1/2*	WHERE SET 3391 40614452 121101	AMOUNT 320 4432 12093 MUDDING NO. SACKS OF CEMENT 275 1500 RECORD OF 1	CASING RECO KIND OF SHOE Guide Guide Float AND CEMENT METHOD USED Helliberta PRODUCTION o. of Qts. or Ga	CUT AND PULLED FROM TING RECORD AND STIMULA als. used, interval	PERFORATI MUD GRAVITY TION treated or sho	ONS AMM	PURPOSE MOUNT OF TUD USED
SIZE 3-3/8* 8-5/8* 5-1/2* SIZE OF HOLE 7-1/2* 1* 7-7/8*	WEIGHT PER FOOT 364 324 17-205 SIZE OF CASING 13-3/8* 5-1/2* 1 xed 5-1/7	WHERE SET 3391 40614452 121101	AMOUNT 320† 4432† 12093† MUDDING NO. SACKS OF CEMENT 27555 \$ 1500 * \$ 500 * Process used, No.	CASING RECO KIND OF SHOE Guide Guide Guide Theat AND CEMENT METHOD USED PRODUCTION o. of Qts. or Ga 2021: to 12	CUT AND PULLED FROM TING RECORD AND STIMULA als. used, interval	MUD GRAVITY TION treated or sho	t.)	PURPOSE MOUNT OF ICD USED

BECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tes or deviation surveys were made, submit report on separate sheet and attach herete TOOLS USED 01 12120t Rotary tools were used from.....feet to..... feet, and from feet to feet Cable tools were used from.....feet to..... feet, and from feet to feet. PRODUCTION 6-14-57 Put to Producing...... 607.89 100 OIL WELL: The production during the first 24 hours was....barrels of liquid of which...... % was emulsion;% water; and% was sediment. A.P.I. 48.1 cerr. Gravity..... liquid Hydrocarbon. Shut in Pressure...........ibs. Length of Time Shut in.... PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE): Southeastern New Mexico Northwestern New Mexico 22961 T. Devonian 12004 T Anhy T. Ojo Alamo..... 23501 T. Salt..... Silurian T. Т Kirtland-Fruitland 29641 T. Montoya.... Т. Farmington.... 30471 T. Yates Simpson T. T. Pictured Cliffs.... 1 B. Yates 31671 McKee.... T. T. Menefee.... Queen..... T. Ellenburger..... T. Point Lookout.... Grayburg..... T. Gr. Wash.... Τ. Mancos.... 4370° San Andres Granite..... Dakota..... Charles Clearfork ::6505t T. T. Morrison.... T. Drinkard..... T. ------Penn. T. 71131 T. T. Т •-----78001 •••••• T. Τ. 94021 Т. T. 114051 T. Miss.... FORMATION RECORD Thickness Thickness From To Formation From To Formation in Feet Cellar 2296 2290 Sand & Shale **inhydrite** 2350 Salt, Anhydrite, Shale & Sand 3047 Anhydrite Sand, Anhydrite, Shale and Salt 1370 Delowite and Anhydrite 5280 380 Lime & Delomite SCREET 1810 Dolemite, Anhydrite & Sam 7470 1600 9070 Delomite, Anhydrite & Shale 9070 1025 1955 Line & Shale 11025 Lime, Sand and Shale 11405 11923 518 Lime, Shale & Chert 11923 12004 g Shale 12004 Dolomite 12120 Total Depth

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

	June 22, 1957		
Company or Operator. Amerada Petroleum Corps	Address Roswell Star Route - Tatum. N.M.		
Name 17-7-6 St. Lagland	Position or Title. Foresan		