

**T
H
S**

(Lease)

Pool.

104

County.

Not Confidential....., 19.....

No. 3, from.....to..... No. 6, from.....to.....

No. 4. from _____ to _____ feet. _____

GOR Based on 22/64" Choke 226 Gty of Oil 48.7 Corrected.
(24 Hour Rate 380 bbls Oil)

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0' feet to 12,135' feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 10-9-58, 19.
OIL WELL: The production during the first 24 hours was 388 barrels of liquid of which 100% was oil; % was emulsion; 8 bbls Acid Water % water; and % was sediment. A.P.I. Gravity 48.7 Corrected
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

SCHLUMBERGER TOPS

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	2307'	T. Devonian	12,102'	T. Ojo Alamo
T. Salt	2354'	T. Silurian		T. Kirtland-Fruitland
B. Salt	2962'	T. Montoya		T. Farmington
T. Yates	3040'	T. Simpson		T. Pictured Cliffs
T. 7 Rivers		T. McKee		T. Menefee
T. Queen		T. Ellenburger		T. Point Lookout
T. Grayburg		T. Gr. Wash		T. Mancos
T. San Andres	4363'	T. Granite		T. Dakota
T. Glorieta	5845'	T.		T. Morrison
T. Intero Clearfork	6500'	T.		T. Penn
T. Tubbs	7106'	T.		T.
T. Abo	7790'	T.		T.
T. Penn	9395'	T.		T.
T. Miss	11494'	T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	6'	6'	Cellar				
6'	2307'	2301'	Sand, Shale				
2307'	2354'	47'	Anhydrite				
2354'	2962'	608'	Salt, Anhydrite, Shale, Sand				
2962'	4363'	1401'	Sand, Shale, Anhydrite				
4363'	5845'	1482'	Lime				
5845'	7790'	1945'	Lime, Shale, Anhydrite				
7790'	9395'	1605'	Dolomite, Shale				
9395'	11054'	1659'	Lime, Shale				
11054'	11494'	440'	Lime, Sand, Shale				
11494'	12006'	512'	Lime, Chert				
12006'	12,102'	96'	Shale				
12102'	12135'	33'	Dolomite				
	12135'		Total Depth.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

October 10, 1958

(Date)

Company or Operator Amerada Petroleum Corporation Address Roswell Star Rt. Tatum, New Mexico
Name H. C. Anderson Position or Title Foreman